

GRTS Survey Designs for a Linear Resource

Thomas Kincaid

May 23, 2012

Contents

1 Preliminaries	1
2 Shapefile attribute data	2
3 Unstratified, equal probability, GRTS survey design	4
4 Stratified, equal probability, GRTS survey design with an oversample	8
5 Stratified, unequal probability, GRTS survey design with an oversample	10
6 Stratified, unequal probability, GRTS survey design with an oversample and a panel structure for survey over time	14

1 Preliminaries

This document presents example GRTS survey designs for a linear resource. The linear resource used in the designs is streams that comprise the Luckiamute watershed in Oregon. Four survey designs will be presented: (1) an unstratified, equal probability design; (2) a stratified, equal probability design with an oversample; (3) a stratified, unequal probability design with an oversample; and (4) a stratified, unequal probability design with an oversample and a panel structure for survey over time. The sampling frame used for the survey designs is contained in either an ESRI shapefile or an sp package object. The frame contains the coordinates for a set of line segments that define the linear resource in addition to attribute data associated with the line segments. The coordinate system for the set of points in the sampling frame is an equal area projection rather than latitude and longitude. An equal area projection is used so that calculation of distance between points is valid.

The initial step is to use the library function to load the spsurvey package. After the package is loaded, a message is printed to the R console indicating that the spsurvey package was loaded successfully.

Load the spsurvey package

```
> # Load the spsurvey package
> library(spsurvey)
>
```

Version 2.1 of the spsurvey package was loaded successfully.

2 Shapefile attribute data

The next step is to read the attribute data from the shapefile. The read.dbf function in the spsurvey package is used to read the attribute (dbf) file in the shapefile and assign it to a data frame named att. The initial six lines in the att data frame are printed using the head function

Next, two attributes, stream type and Strahler stream order, that will be used to define, respectively, stratum codes and unequal selection probability (multidensity) categories for the survey designs are examined. Stream type is contained in a variable named "perint", and Strahler stream order is contained in a variable named "strahcat". For stream type, streams are classified as either perennial or intermittent. For Strahler stream order, streams are classified as either first order ("1st"), second order ("2nd"), or third order and higher ("3rd+"). The table and addmargin functions are used to produce a table displaying number of stream segments for each combination of values for the strata and multidensity category variables.

Finally, frame stream length is summarized for the strata and multidensity category attributes. Note that stream length measured in kilometers is contained in the variable named "length_km". The tapply function is used to calculate total stream length for each combination of stream type and Strahler stream order. The addmargins function is applied to the output from tapply to calculate stream length for each category of stream type and Strahler stream order, and the round function is used to round value to two decimal places. Finally, the resulting cross-tabulation of sum of stream length in kilometers for Strahler stream order and stream type is displayed.

Read the attribute table from the shapefile

```
> # Read the attribute table from the shapefile
> att <- read.dbf("luck_ash")
>
```

Display the initial six lines in the attribute data frame

```
> # Display the initial six lines in the attribute data frame
> head(att)
```

```
      perint strahcat length_km length_mdm
1  Perennial    2nd    2.326    2326
2 Intermittent  1st    0.579     579
3 Intermittent  1st    0.780     780
4  Perennial    1st    1.876    1876
5 Intermittent  1st    1.001    1001
6  Perennial    1st    1.646    1646
```

```
>
```

Display number of stream segments cross-classified by the strata and multidensity category variables

```
> # Display number of stream segments cross-classified by the strata and
> # multidensity category variables
>
> addmargins(table("Stream Type"=att$perint, "Strahler Order"=att$strahcat))
```

```
      Strahler Order
Stream Type  1st 2nd 3rd+ Sum
  Intermittent 137 20  2 159
  Perennial    104 78  88 270
  Sum          241 98  90 429
```

```
>
```

Summarize frame stream length by stratum and multidensity category

```
> # Summarize frame stream length by stratum and multidensity category
> temp <- tapply(att$length_km, list(att$perint, att$strahcat), sum)
> temp <- round(addmargins(temp), 2)
> names(dimnames(temp)) <- list("Stream Type", "Strahler Order")
> temp
```

```
      Strahler Order
Stream Type  1st  2nd  3rd+ Sum
  Intermittent 306 20.5  3.03 329
  Perennial    201 133.1 159.79 493
  Sum          506 153.6 162.82 822
```

>

Streams in the Luckiamute watershed are displayed in Figure 1 classified by stream type and in Figure 2 classified by Strahler stream order category. To produce the figure, first the `read.shape` function in the `spsurvey` package is used to read the shapefile and assign it to an object named `shp`. The `shp` object takes the form of a spatial data object defined in the `sp` package. Specifically, `shp` belongs to class "SpatialLinesDataFrame". For further information about spatial data objects, see documentation for the `sp` package. The `spplot` function in the `sp` package is used to create the figures.

Read the shapefile

```
> shp <- read.shape("luck_ash")
```

Plot streams in the Luckiamute watershed classified by stream type

```
> spplot(shp, zcol="perint", col.regions=c("red", "blue"))
```

Plot streams in the Luckiamute watershed classified by Strahler stream order

```
> spplot(shp, zcol="strahcat", col.regions=c("red", "green", "blue"))
```

3 Unstratified, equal probability, GRTS survey design

The first survey design is an unstratified, equal probability design. The `set.seed` function is called so that, if necessary, the designs can be replicated.

The initial step is to create a list named `Equaldsgn` that contains information for specifying the survey design. Since the survey design is unstratified, the list contains a single item named "None" that also is a list. The "None" list includes two items: `panel`, which is used to specify the sample size for each panel, and `seltype`, which is used to input the type of random selection for the design. For this example, `panel` is assigned a single value named "PanelOne" that is set equal to 50, and `seltype` is assigned the value "Equal", which indicates equal probability selection.

The `grts` function in the `spsurvey` package is called to select the survey design. The following arguments are included in the call to `grts`: (1) `design`: the named list of stratum design specifications, which is assigned the `Equaldsgn` list; (2) `DesignID`: name for the design, which is used to create a site ID for each site and is assigned the value "EQUAL"; (3) `type.frame`: the type of frame, which is assigned the value "linear" to indicate a linear resource; (4) `src.frame`: source of the frame, which is assigned the value "shapefile" to indicate a shapefile frame; (5) `in.shape`: name of the input shapefile, which is assigned the value "luck_ash"; (6) `att.frame`: the data frame of attributes associated with elements in the frame, which is




Figure 1: Streams in the Luckiamute Watershed Classified by Stream Type.




Figure 2: Streams in the Luckiamute Watershed Classified by Strahler Stream Order Category.

assigned the att data frame; and (7) shapefile: option to create a shapefile containing the survey design information, which is assigned FALSE.

During execution of the grts function, messages are printed that indicate the initial number of hierarchical levels used for the GRTS grid, the current number of levels, and the final number of levels. The set of messages is printed for each stratum, and is labeled with the stratum name. For this example, the set of messages is labeled "None", i.e., the name used in the Equaldsgn list. Upon completion of the call to grts, the initial six sites for the survey design and a design summary are printed.

Call the set.seed function so that the design can be replicated

```
> # Call the set.seed function so that the survey designs can be replicate
> set.seed(19742003)
>
```

Create the design list

```
> # Create the design list
> Equaldsgn <- list(None=list(panel=c(PanelOne=50), seltype="Equal"))
>
```

Select the sample

```
> Equalsites <- grts(design=Equaldsgn,
+                   DesignID="EQUAL",
+                   type.frame="linear",
+                   src.frame="shapefile",
+                   in.shape="luck_ash",
+                   att.frame=att,
+                   shapefile=FALSE)
```

Stratum: None

Initial number of levels: 3

Current number of levels: 3

Current number of levels: 4

Final number of levels: 4

Print the initial six lines of the survey design

```
> # Print the initial six lines of the survey design
> head(Equalsites@data)
```

	siteID	xcoord	ycoord	mdcaty	wgt	stratum	panel	EvalStatus	EvalReason
1	EQUAL-01	-2151443	2734150	Equal	16450	None	PanelOne	NotEval	
2	EQUAL-02	-2144834	2735275	Equal	16450	None	PanelOne	NotEval	
3	EQUAL-03	-2143643	2743030	Equal	16450	None	PanelOne	NotEval	
4	EQUAL-04	-2124733	2722643	Equal	16450	None	PanelOne	NotEval	
5	EQUAL-05	-2130690	2732801	Equal	16450	None	PanelOne	NotEval	
6	EQUAL-06	-2140629	2722765	Equal	16450	None	PanelOne	NotEval	

	perint	strahcat	length_km
1	Perennial	1st	1.91
2	Intermittent	1st	1.50
3	Perennial	2nd	2.51
4	Perennial	3rd+	2.49
5	Intermittent	1st	2.34
6	Perennial	3rd+	1.79

>

Print the survey design summary

```
> # Print the survey design summary
> dsgnsum(Equalsites)
```

Design Summary: Number of Sites

stratum	None	Sum
	50	50

>

4 Stratified, equal probability, GRTS survey design with an oversample

The second survey design is a stratified, equal probability design with an oversample. The stream type attribute is used to identify strata. List Stratdsgn is assigned design specifications. Since the survey design is stratified, Stratdsgn includes two lists named "Perennial" and "Intermittent" that contains three items: panel, seltype, and over. Note that the names for the two lists match the levels of the stratum variable. For both lists, the values for panel and seltype are the same as the ones used for the equal probability design. The third item, over, assigns the value 50 for size of the oversample. An oversample provides additional sample sites to replace sites that cannot be used, e.g., to replace sites in the sample that are not accessible.

For this survey design, a shapefile will be used as the sampling frame. The following arguments are included in the call to grts: (1) design: assigned the Stratdsgn list; (2) DesignID: assigned the value "STRATIFIED"; (3) type.frame: assigned the value "linear"; (4) src.frame: assigned the value "shapefile"; (5) in.shape: assigned the value "luck_ash"; (6) att.frame: assigned the att data frame; (7) stratum: name of the column in the attributes data frame that identifies the stratum code for each element in the frame, which is assigned the value "perint"; and (8) shapefile: assigned the value FALSE. Upon completion of the call to grts, the initial six sites for the survey design and a design summary are printed.

Create the design list

```
> Stratdsgn <- list(Perennial=list(panel=c(PanelOne=50),
+                               seltype="Equal",
+                               over=50),
+                 Intermittent=list(panel=c(PanelOne=50),
+                                   seltype="Equal",
+                                   over=50))
```

Select the sample

```
> Stratsites <- grts(design=Stratdsgn,
+                   DesignID="STRATIFIED",
+                   type.frame="linear",
+                   src.frame="shapefile",
+                   in.shape="luck_ash",
+                   att.frame=att,
+                   stratum="perint",
+                   shapefile=FALSE)
```

Stratum: Perennial

Initial number of levels: 4

Current number of levels: 4

Current number of levels: 5

Final number of levels: 5

Stratum: Intermittent

Initial number of levels: 4

Current number of levels: 4

Current number of levels: 5

Final number of levels: 5

Print the initial six lines of the survey design

```
> # Print the initial six lines of the survey design
> head(Stratsites@data)
```

```

      siteID  xcoord  ycoord  mdcaty  wgt  stratum  panel  EvalStatus
1 STRATIFIED-001 -2137017 2737685 Equal 9868 Perennial PanelOne NotEval
2 STRATIFIED-002 -2147634 2745811 Equal 9868 Perennial PanelOne NotEval
3 STRATIFIED-003 -2142407 2728762 Equal 9868 Perennial PanelOne NotEval
4 STRATIFIED-004 -2147848 2732473 Equal 9868 Perennial PanelOne NotEval
5 STRATIFIED-005 -2131391 2741066 Equal 9868 Perennial PanelOne NotEval
6 STRATIFIED-006 -2139311 2724986 Equal 9868 Perennial PanelOne NotEval
  EvalReason strahcat length_km
1              1st      1.781
2              2nd      3.100
3              1st      6.384
4             3rd+      0.611
5              1st      2.895
6             3rd+      1.653

```

>

Print the survey design summary

```

> # Print the survey design summary
> dsgnsum(Stratsites)

```

Design Summary: Number of Sites Classified by panel and stratum

panel	stratum		Sum
	Perennial	Intermittent	
OverSamp	50	50	100
PanelOne	50	50	100
Sum	100	100	200

>

5 Stratified, unequal probability, GRTS survey design with an oversample

The third survey design is a stratified, unequal probability design with an oversample. As for the second survey design, the stream type attribute is used to identify strata. Strahler order categories are used to identify multidensity categories. List Unequaldsgn is assigned design specifications. Unequaldsgn includes the same two lists with three items (panel, seltype, and over) as used for the stratified, equal probability design plus a value for caty.n. For both lists, panel specifies a single panel, and seltype is assigned "Unequal" to indicate

unequal probability sampling. Note that the value 0 is assigned to over for the "Intermittent" stratum, i.e., no oversample. The over item could have been omitted from the list for "Intermittent". The vector assigned to caty.n specifies sample sizes for each of the three multidensity categories. Note that the sum of values provided in caty.n must equal the value in panel.

For this survey design, an sp package object will be used as the sampling frame. Recall that the read.shape function was used to read the shapefile and assign its output to an sp object named shp. The following arguments are included in the call to grts: (1) design: assigned the Unequaldsgn list; (2) DesignID: assigned the value "UNEQUAL"; (3) type.frame: assigned the value "linear"; (4) src.frame: assigned the value "sp.object" to indicate that the sampling frame is provided by an sp object; (5) sp.object: name of the sp object, which is assigned the shp object; (6) att.frame: assigned the att data frame; (7) stratum: assigned the value "perint"; (8) mdcaty: name of the column in the attributes data frame that identifies the unequal probability category for each element in the frame, which is assigned the value "strahcat"; (9) shapefile: assigned the value FALSE. Upon completion of the call to grts, the initial six sites for the survey design and a design summary are printed.

Create the design list

```
> Unequaldsgn <- list(Perennial=list(panel=c(PanelOne=75),
+                               seltype="Unequal",
+                               caty.n=c("1st"=25, "2nd"=25, "3rd+"=25),
+                               over=36),
+                    Intermittent=list(panel=c(PanelOne=32),
+                                       seltype="Unequal",
+                                       caty.n=c("1st"=25, "2nd"=5, "3rd+"=2),
+                                       over=0))
```

Select the sample

```
> Unequalsites <- grts(design=Unequaldsgn,
+                      DesignID="UNEQUAL",
+                      type.frame="linear",
+                      src.frame="sp.object",
+                      sp.object=shp,
+                      att.frame=att,
+                      stratum="perint",
+                      mdcaty="strahcat",
+                      shapefile=FALSE)
```

Stratum: Perennial

Initial number of levels: 4

Current number of levels: 4

Current number of levels: 5

Final number of levels: 5

Stratum: Intermittent

Initial number of levels: 3

Current number of levels: 3

Current number of levels: 4

Current number of levels: 5

Final number of levels: 5

Print the initial six lines of the survey design

```
> # Print the initial six lines of the survey design
> head(Unequalsites@data)
```

	siteID	xcoord	ycoord	mdcaty	wgt	stratum	panel	EvalStatus
1	UNEQUAL-001	-2127979	2739386	2nd	5324	Perennial	PanelOne	NotEval
2	UNEQUAL-002	-2151221	2737138	2nd	5324	Perennial	PanelOne	NotEval
3	UNEQUAL-003	-2143315	2724152	3rd+	6392	Perennial	PanelOne	NotEval
4	UNEQUAL-004	-2148760	2734240	3rd+	6392	Perennial	PanelOne	NotEval
5	UNEQUAL-005	-2133077	2740938	2nd	5324	Perennial	PanelOne	NotEval
6	UNEQUAL-006	-2129966	2736424	3rd+	6392	Perennial	PanelOne	NotEval

	EvalReason	length_km
1		0.279
2		2.958
3		4.612
4		2.141
5		2.640
6		2.294

>

Print the survey design summary

```
> # Print the survey design summary
> dsgnsum(Unequalsites)
```

Design Summary: Number of Sites Classified by mdcaty (Multidensity Category) and stratum

	stratum		
mdcaty	Perennial	Intermittent	Sum
1st	32	25	57

2nd	39	5	44
3rd+	40	2	42
Sum	111	32	143

Design Summary: Number of Sites Classified by panel and stratum

	stratum		
panel	Perennial	Intermittent	Sum
OverSamp	36	0	36
PanelOne	75	32	107
Sum	111	32	143

Design Summary: Number of Sites Classified by mdcaty (Multidensity Category), panel, and stratum

, , stratum = Perennial

	panel		
mdcaty	OverSamp	PanelOne	Sum
1st	10	22	32
2nd	11	28	39
3rd+	15	25	40
Sum	36	75	111

, , stratum = Intermittent

	panel		
mdcaty	OverSamp	PanelOne	Sum
1st	0	25	25
2nd	0	5	5
3rd+	0	2	2
Sum	0	32	32

, , stratum = Sum

	panel		
mdcaty	OverSamp	PanelOne	Sum
1st	10	47	57
2nd	11	33	44
3rd+	15	27	42
Sum	36	107	143

>

6 Stratified, unequal probability, GRTS survey design with an oversample and a panel structure for survey over time

The fourth survey design is a stratified, unequal probability design with an oversample and a panel structure for survey over time. List `Paneldsgn` is assigned design specifications. Analogous to the stratified, unequal probability design, `Paneldsgn` includes two lists named "Perennial" and "Intermittent". For the "Perennial" stratum, a vector identifying sample sizes for three panels is assigned to `panel`. For the "Intermittent" stratum, the sample size for a single panel named "YearOnce" is assigned to `panel`. The value "Unequal" is assigned to `seltype` for both lists, which indicates unequal selection probabilities. For both lists, the third item, `caty.n`, assigns sample sizes for each of the three multidensity categories. Again, note that the sum of sample sizes provided in `caty.n` must equal the sum of sample sizes in `panel`. For the "Perennial" stratum, the value 50 is assigned to `over`, which specifies an oversample of 50 sites. No oversample is specified for the "Intermittent" stratum, and so `over` is not included in the list. The `grts` function attempts to distribute the oversample proportionately among sample sizes for the multidensity categories. If the oversample proportion for one or more categories is not a whole number, a warning message is printed and the proportion is rounded to the next higher integer. For the "Perennial" stratum, the oversample is not proportionate to the multidensity category sample sizes, and the warning message is printed by calling the `warnings` function.

For this survey design, a shapefile will be used as the sampling frame. The following arguments are included in the call to `grts`: (1) `design`: assigned the `Paneldsgn` list; (2) `DesignID`: assigned the value "UNEQUAL"; (3) `type.frame`: assigned the value "linear"; (4) `src.frame`: assigned the value "shapefile"; (5) `in.shape`: assigned the value "luck_ash"; (6) `att.frame`: assigned the `att` data frame; (7) `stratum`: assigned the value "perint"; (8) `mdcaty`: assigned the value "strahcat"; (9) `shapefile`: assigned the value FALSE. Upon completion of the call to `grts`, the initial six sites for the survey design and a design summary are printed.

Create the design list

```
> Paneldsgn <- list(Perennial=list(panel=c(Year1=17, Year2=17, YearAll=16),
+                                   seltype="Unequal",
+                                   caty.n=c("1st"=15, "2nd"=15, "3rd+"=20),
+                                   over=50),
+                 Intermittent=list(panel=c(YearOnce=27),
+                                   seltype="Unequal",
+                                   caty.n=c("1st"=20, "2nd"=5, "3rd+"=2)))
```

Select the sample

```
> Panelsites <- grts(design=Paneldsgn,
+                   DesignID="UNEQUAL",
```

```

+         type.frame="linear",
+         src.frame="shapefile",
+         in.shape="luck_ash",
+         att.frame=att,
+         stratum="perint",
+         mdcaty="strahcat",
+         shapefile=FALSE)

```

Stratum: Perennial

```

Initial number of levels: 4
Current number of levels: 4
Current number of levels: 5
Current number of levels: 6
Final number of levels: 6

```

Stratum: Intermittent

```

Initial number of levels: 3
Current number of levels: 3
Current number of levels: 4
Current number of levels: 5
Final number of levels: 5

```

Print the warning message

```

> # Print the warning message
> warnings()
>

```

Warning message:

```

In grts(design = Paneldsgn, DesignID = "UNEQUAL", type.frame = "linear", :

```

```

Oversample size is not proportional to category sample sizes for stratum
"Perennial".

```

Print the initial six lines of the survey design

```

> # Print the initial six lines of the survey design
> head(Panelsites@data)

```

	siteID	xcoord	ycoord	mdcaty	wgt	stratum	panel	EvalStatus
1	UNEQUAL-001	-2148784	2745360	1st	13369	Perennial	Year1	NotEval
2	UNEQUAL-002	-2152267	2736268	1st	13369	Perennial	Year1	NotEval

```

3 UNEQUAL-003 -2128882 2729846 3rd+ 7990 Perennial Year1 NotEval
4 UNEQUAL-004 -2146814 2731447 3rd+ 7990 Perennial Year1 NotEval
5 UNEQUAL-005 -2141802 2742260 3rd+ 7990 Perennial Year1 NotEval
6 UNEQUAL-006 -2147981 2732448 1st 13369 Perennial Year1 NotEval

```

```

EvalReason length_km
1          1.86
2          3.71
3          4.83
4          2.26
5          1.27
6          3.03

```

>

Print the survey design summary

```

> # Print the survey design summary
> dsgnsum(Panelsites)

```

Design Summary: Number of Sites Classified by mdcaty (Multidensity Category) and stratum

		stratum		
mdcaty	Perennial	Intermittent	Sum	
1st	30	19	49	
2nd	28	5	33	
3rd+	42	3	45	
Sum	100	27	127	

Design Summary: Number of Sites Classified by panel and stratum

		stratum		
panel	Perennial	Intermittent	Sum	
OverSamp	50	0	50	
Year1	17	0	17	
Year2	17	0	17	
YearAll	16	0	16	
YearOnce	0	27	27	
Sum	100	27	127	

Design Summary: Number of Sites Classified by mdcaty (Multidensity Category), panel, and stratum

```
, , stratum = Perennial
```

```
    panel
mdcaty OverSamp Year1 Year2 YearAll YearOnce Sum
  1st      16     5     5      4      0  30
  2nd      17     4     4      3      0  28
  3rd+     17     8     8      9      0  42
  Sum      50    17    17     16      0 100
```

```
, , stratum = Intermittent
```

```
    panel
mdcaty OverSamp Year1 Year2 YearAll YearOnce Sum
  1st      0     0     0      0     19  19
  2nd      0     0     0      0     5   5
  3rd+     0     0     0      0     3   3
  Sum      0     0     0      0    27  27
```

```
, , stratum = Sum
```

```
    panel
mdcaty OverSamp Year1 Year2 YearAll YearOnce Sum
  1st      16     5     5      4     19  49
  2nd      17     4     4      3     5  33
  3rd+     17     8     8      9     3  45
  Sum      50    17    17     16    27 127
```

```
>
```