

US EPA ARCHIVE DOCUMENT

CONSOLIDATED CHECKLIST  
for the  
Burning of Hazardous Waste in Boilers and Industrial Furnaces  
as of June 30, 1994

Notes 1) This checklist consolidates changes to the Federal code addressed by the following Boilers and Industrial Furnaces (BIF) checklists that have occurred through June 30, 1994:

- Revision Checklist 85 [56 FR 7134 (February 21, 1991)];
- Revision Checklist 94 [56 FR 32688 (July 17, 1991)];
- Revision Checklist 96 [56 FR 42504 (August 27, 1991)];
- Revision Checklist 98 [56 FR 43874 (September 5, 1991)];
- Revision Checklist 105 [57 FR 27880 (June 22, 1992)];
- Revision Checklist 110 [57 FR 37284 (August 18, 1992)];
- Revision Checklist 111 [57 FR 38558 (August 25, 1992)];
- Revision Checklist 114 [57 FR 44999 (September 30, 1992)];
- Revision Checklist 125 [58 FR 38816 (July 20, 1993)] and
- Revision Checklist 127 [58 FR 59598 (November 9, 1993)].

Note that Revision Checklists 105 and 110, which address Coke By-Products, are included in this consolidated checklist because they also affect the BIF rule.

2) Note that the regulations addressed by this checklist typically do not make a distinction between the various types of burning devices. However, the provisions in the regulations as they apply to sludge fryers, carbon regeneration units, infrared incinerators, and plasma arc incinerators are considered to be non-HSWA requirements, while the regulations as they apply to all other types of burning devices are HSWA provisions. EPA will implement the HSWA requirements in authorized States until the States modify their programs and such modifications are approved by EPA. The non-HSWA requirements are applicable only in those States which are unauthorized. In authorized States, the non-HSWA requirements will not be applicable until the States revise their programs to adopt equivalent requirements under State law.

3) Revision Checklist 98 addresses an administrative stay of the permitting standards for BIFs adopted pursuant to the February 21, 1991 (56 FR 7134; Revision Checklist 85) final rule as it applies to coke ovens burning certain hazardous wastes from the coke by-products recovery process. This administrative stay has been removed by Revision Checklist 105 (57 FR 27880; June 22, 1992) and, therefore, should not be adopted by States.

4) The final rule addressed by Revision Checklist 125 was promulgated pursuant to the Clean Air Act, rather than the Resource Conservation and Recovery Act, and primarily amends regulations in 40 CFR Parts 51 and 52. However, this rule also makes conforming changes to 40 CFR Parts 260 and 266 to ensure that the guidelines for air quality modeling and screening for boilers and industrial furnaces burning hazardous waste are consistent with the guidelines in 40 CFR Part 51. Only the changes to 40 CFR Parts 260 and 266 are included in Revision Checklist 125 and in this consolidated checklist. These revisions are necessary. Therefore, Revision Checklist 125 has been developed to help States maintain consistency with the Federal regulations. Note that States do not have to adopt the changes to 40 CFR Parts 51 and 52 to make the Part 260 and 266 changes. Rather, States should reference Appendix W, Part 51 at 266.104(e)(3) and 266.106(h).

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

Note that EPA's Office of Solid Waste is treating the changes made by the Air rule to 40 CFR Parts 260 and 266 as HSWA provisions because they amend the BIF regulations promulgated under HSWA.

5) Although Revision Checklist 127 is designated as optional, EPA strongly recommends that States adopt the less stringent requirements of this administrative stay because the nonmetal limits affected by the stay are extremely conservative and were based on unintended mistaken assumptions. This rule replaces the current nonmetal limits needed to qualify for the Bevill exemption, as specified in the February 21, 1991 rule (Revision Checklist 85), with the land disposal restriction (LDR) limits for underlying constituents in nonwastewaters pending further administrative action to establish appropriate health-based levels.

Note that the administrative stay is conditioned on compliance with the interim LDR exemption values. Noncompliance with those values would mean that the owner or operator of the Bevill device is no longer meeting the conditions of the administrative stay and, therefore, must comply with the comparison test in § 266.112(b)(1), in order to qualify for the exclusion in § 266.112. If the owner or operator meets neither the conditions of the stay nor the comparison test, then the residue would be subject to regulation as hazardous waste. Additionally, the stay does not affect the application of the procedural requirements in 266.112(b)(2) except as outlined in 58 FR 59600, column 3, sections V. A-D.

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER
<b>PART 260 - HAZARDOUS WASTE MANAGEMENT SYSTEM: GENERAL</b>							
<b>SUBPART B - DEFINITIONS</b>							
<b>DEFINITIONS</b>							
change "Parts 260 through 265 and 268" to "Parts 260 through 266 and 268"	85	260.10(intro)	260.10(intro)	X			
"carbon regeneration unit"	85	260.10	260.10	X			
revise "incinerator"	85	260.10(1)&(2)	260.10(1)&(2)	X			
replace "controlled flame devices" with "thermal treatment" in introductory text of the definition for "industrial furnace"	85	260.10	260.10	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
redesignate paragraph (12) in the definition for "industrial furnace" as paragraph (13); add new paragraph (12) that adds halogen acid furnaces to the list of devices considered industrial furnaces	85	260.10(12)&(13)	260.10(12)&(13)	X			
"infrared incinerator"	85,111	260.10	260.10	X			
"plasma arc incinerator"	85,111	260.10	260.10	X			
"sludge dryer"	85	260.10	260.10	X			

**REFERENCES**

add to first of set listings in alphabetical order a reference to the October 1992 version of "U.S. EPA, Screening Procedures for Estimating the Air Quality Impact of Stationary Sources"	85,125	260.11(a)	260.11(a)	X			
--	--------	-----------	-----------	---	--	--	--

**SUBPART C - RULEMAKING PETITIONS**

**GENERAL**

replace "265" with "266" in the first sentence	111	260.20(a)	No State analog			X	
--	-----	-----------	-----------------	--	--	---	--

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
<b>PART 261 - IDENTIFICATION AND LISTING OF HAZARDOUS WASTE</b>							
<b>SUBPART A - GENERAL</b>							
<b>DEFINITION OF SOLID WASTE</b>							
1 redesignate (d)(2) as (d)(3); add new paragraph regarding secondary materials fed to a halogen acid furnace that exhibit a characteristic or are a listed waste; exception for brominated material that meets certain criteria	85, 94,96	261.2(d)(2)	261.2(d)(2)	X			
material must contain a bromine concentration of at least 45%	96	261.2(d)(2)(i)	261.2(d)(2)(i)	X			
material must contain less than a total of 1% of toxic organic compounds listed in Appendix VIII	96	261.2(d)(2)(ii)	261.2(d)(2)(ii)	X			
material is processed continually on-site in the halogen acid furnace via direct conveyance	96	261.2(d)(2)(iii)	261.2(d)(2)(iii)	X			
redesignate old 261.2(d)(2) as 261.2(d)(3)	85,94	261.2(d)(3)	261.2(d)(3)				
change "paragraph" to "paragraphs"; insert "and (d)(2)" after "(d)(1)"	111	261.2(e)(2)(iv)	261.2(d)(2)(iv)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
<b>DEFINITION OF HAZARDOUS WASTE</b>							
2 replace "261.6(a)(3)(v) through (ix)" with "261.6(a)(3)(v) through (viii)"	94,96	261.3(c)(2)(ii)(B)	261.3(c)(2)(ii)(B)	X			
<b>EXCLUSIONS</b>							
† add exclusion for K060, K087, K141, K142, K143, K144, K145, K147, K148 and other wastes from coke by-products that are hazardous only because they exhibit the Toxicity Characteristic when recycled as specified; exclusion is conditioned on there being no land disposal of the wastes from point of generation to recycling point	85, 105,110	261.4(a)(10)	261.4(a)(10)	X			
insert "except as provided by §266.112 of this chapter for facilities that burn or process hazardous waste" at end of paragraph	85	261.4(b)(4)	261.4(b)(4)	X			
revise first sentence to include phosphate rock and overburden from the mining of uranium ore in the existing parenthetical phrase; insert "except as provided by §266.112 of this chapter for facilities that burn or process hazardous waste" at end of first sentence	85	261.4(b)(7)	261.4(b)(7)	X			
add "except as provided by §266.112 of this chapter for facilities that burn or process hazardous waste" to end of paragraph	85	261.4(b)(8)	261.4(b)(8)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIV-ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE
<b>REQUIREMENTS FOR RECYCLABLE MATERIALS</b>							
replace the letter "G" with "H"	94	261.6(a)(2)	261.6(a)(2)	X			
replace "Subpart D" with "Subpart H"	94	261.6(a)(2)(ii)	261.6(a)(2)(ii)	X			
remove existing paragraph 261.6(a)(3)(vii) and redesignate 261.6(a)(3)(viii) as 261.6(a)(3)(vii)	85	261.6(a)(3)(vii)	261.6(a)(3)(vii)	X			
redesignate 261.6(a)(3)(ix) as 261.6(a)(3)(viii)	85	261.6(a)(3)(viii)	NA	Not applicable due to changes made by CL112			
<b>SUBPART D - LISTS OF HAZARDOUS WASTES</b>							
<b>HAZARDOUS WASTES FROM SPECIFIC SOURCES</b>							
add K141-K145, K147 and K148 in alphanumeric order to the subgroup "Coking" as specified at 57 FR 37305	110	261.32	261.32	X			
<b>APPENDIX VII TO PART 261</b>							
<b>BASIS FOR LISTING HAZARDOUS WASTE</b>							
add K141-K145, K147 and K148 in alphanumeric order as specified at 57 FR 37305	110	261, Appendix VII	261, Appendix VII	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE

**PART 264 - STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE  
TREATMENT, STORAGE, AND DISPOSAL FACILITIES**

**SUBPART A - GENERAL**

**PURPOSE, SCOPE, AND APPLICABILITY**

change "subparts C, D, F, or G" to "subparts C, F, G, or H"	111	264.1(g)(2)	264.1(g)(2)	X			
---	-----	-------------	-------------	---	--	--	--

**SUBPART G - CLOSURE AND POST-CLOSURE**

**CLOSURE OF PLAN; AMENDMENT OF PLAN**

add sentence regarding written notification of Regional Administrator at least 45 days prior to partial or final closure of a boiler or industrial furnace	85	264.112(d)(1)	264.112(d)(1)	X			
--	----	---------------	---------------	---	--	--	--

**SUBPART O - INCINERATORS**

**APPLICABILITY**

regulations apply to owners and operators of hazardous waste incinerators (as defined in 260.10) except as 264.1 provides otherwise	85	264.340(a)	264.340(a)	X			
---	----	------------	------------	---	--	--	--

**PART 265 - INTERIM STATUS STANDARDS FOR OWNERS AND OPERATORS OF  
HAZARDOUS WASTE TREATMENT, STORAGE AND DISPOSAL FACILITIES**

**SUBPART A - GENERAL**

**PURPOSE, SCOPE, AND APPLICABILITY**

change "subparts C, D, F, or G" to "subparts C, F, G, or H"	111	265.1(c)(6)	265.1(c)(6)	X			
---	-----	-------------	-------------	---	--	--	--

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
<b>SUBPART G - CLOSURE AND POST-CLOSURE</b>							
<b>CLOSURE PLAN; AMENDMENT OF PLAN</b>							
insert "or by six months after the effective date of the rule that first subjects a facility to provisions of this section" after "By May 19, 1981"	85	265.112(a)	265.112(a)	X			
add sentence regarding submittal of closure plan at least 45 days prior to beginning partial or final closure of a boiler or industrial furnace; add sentence regarding written notification at least 45 days prior to beginning partial or final closure of a boiler or industrial furnace when the owner or operator has an approved closure plan	85	265.112(d)(1)	265.112(d)(1)	X			
3 date when owner or operator "expects to begin closure" must be either:	85,96	265.112(d)(2)	265.112(d)(2)	X			
3 compliance dates for hazardous waste units receiving final or most recent volume of hazardous wastes; extension by Regional Administrator, or	85,96	265.112(d)(2)(i)	265.112(d)(2)(i)	X			
3 compliance dates for hazardous waste units meeting 265.113(d) requirements receiving final volume or most recent volume nonhazardous wastes; extension by Regional Administrator	85,96	265.112(d)(2)(ii)	265.112(d)(2)(ii)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
<b>CLOSURE; TIME ALLOWED FOR CLOSURE</b>							
3 within 90 days after receiving final volume of hazardous or non-hazardous wastes if owner/operator complies with 265.113(d)&(e) requirements or 90 days after approval of closure plan, whichever is later; criteria for extension by Regional Administrator	85,96	265.113(a)	265.113(a)	X			
3 complete partial and final closure within 180 days after receiving final volume of hazardous or non-hazardous waste if owner/operator complies with 265.113(d)&(e) requirements or 180 days after approval of closure plan, whichever is later; extension by Regional Administrator	85,96	265.113(b)	265.113(b)	X			
<b>SUBPART O - INCINERATORS</b>							
<b>APPLICABILITY</b>							
regulations apply to owners and operators of hazardous waste incinerators (as defined in 260.10) except as 264.1 provides otherwise	85	265.340(a)	265.340(a)	X			
<b>SUBPART P - THERMAL TREATMENT</b>							
<b>OTHER THERMAL TREATMENT</b>							
delete "." at the end and insert ", and Subpart H of Part 266, if the unit is a boiler or an industrial furnace as defined in §260.10."	94	265.370	265.370	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
<b>PART 266 - STANDARDS FOR THE MANAGEMENT OF SPECIFIC HAZARDOUS WASTES AND SPECIFIC TYPES OF HAZARDOUS WASTE MANAGEMENT FACILITIES</b>							
<b>SUBPART D - HAZARDOUS WASTE BURNED FOR ENERGY RECOVERY</b>							
remove and reserve Subpart D	85	266.30-266.35	266.30-266.35	X			
<b>4 SUBPART E - USED OIL BURNED FOR ENERGY RECOVERY</b>							
APPLICABILITY							
5 replace "Subpart D of Part 266" with "Subpart H of Part 266"	94,96	266.40(c)	reserved				These paragraphs were reserved as per CL112, a checklist for which Delaware is also applying
5 replace "Subpart D" with "Subpart H"	94,96	266.40(d)	reserved				
<b>SUBPART H - HAZARDOUS WASTE BURNED IN BOILERS AND INDUSTRIAL FURNACES</b>							
APPLICABILITY							
6 regulations apply to hazardous waste burned or processed in a boiler or industrial furnace, irrespective of purpose, except as 266.100(b),(c),(d) and (f) provide; definition of "burn"; 266.104-266.107 emissions standards apply to interim status or permitted facilities	85,96,†98,†105,111	266.100(a)	266.100(a)	X			Note that Delaware is not applying for CL 98.
hazardous wastes and facilities not subject to regulation under Subpart H:	85	266.100(b)	266.100(b)	X			
7 used oil burned for energy recovery that is hazardous solely because it exhibits a characteristic; regulated under 266, Subpart E	85	266.100(b)(1)	266.100(b)(1)	X			
gas recovered from landfills and burned for energy recovery	85,94	266.100(b)(2)	266.100(b)(2)	X			

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
gas recovered from landfills and burned for energy recovery	85,94	266.100(b)(2)	266.100(b)(2)	X			
exempt hazardous wastes under 261.4 and 261.6(a)(3)(v)-(viii); CESQG hazardous wastes under 261.5	85,94	266.100(b)(3)	266.100(b)(3)	X			
coke ovens burning only K087	85	266.100(b)(4)	266.100(b)(4)	X			
owners and operators of smelting, melting and refining furnaces processing hazardous waste solely for metal recovery conditionally exempt, except for 266.101 and 266.112	85	266.100(c)	266.100(c)	X			
requirements for exemption from 266.1022 through 266.111 for owner or operator of metal recovery furnace; owner or operator of a lead or a nickel-chromium recovery furnace, or certain metal recovery furnaces subject to 266.100(c)(3) requirements	85,96	266.100(c)(1)	266.100(c)(1)	X			
one-time written notice indicating:	85	266.100(c)(1)(i)	266.100(c)(1)(i)	X			
owner or operator claims 266.100(c) exemption	85	266.100(c)(1)(i)(A)	266.100(c)(1)(i)(A)	X			
metal recovery as per 266.100(c)(2) provisions	85	266.100(c)(1)(i)(B)	266.100(c)(1)(i)(B)	X			
recoverable levels of metals	85	266.100(c)(1)(i)(C)	266.100(c)(1)(i)(C)	X			
compliance with 266.100(c) sampling and analysis and recordkeeping requirements	85	266.100(c)(1)(i)(D)	266.100(c)(1)(i)(D)	X			

US EPA ARCHIVE DOCUMENT

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
sample and analyze hazardous waste and other feedstocks as necessary using specified procedures or alternative methods that meet or exceed SW-846 method performance capabilities; situation where "best available method" is used	85,96	266.100(c)(1)(ii)	266.100(c)(1)(ii)	X			
maintain specified records at facility for at least three years	85	266.100(c)(1)(iii)	266.100(c)(1)(iii)	X			
criteria under which a hazardous waste is not processed solely for metal recovery	85	266.100(c)(2)	266.100(c)(2)	X			
total concentration of 261, Appendix VIII organic compounds exceeds 500 ppm by weight and are considered burned for destruction; reduction of organic compound concentration to the 500 ppm limit by bona fide treatment; blending for dilution to meet the 500 ppm limit is prohibited; retention of documentation in records required by 266.100(c)(1)(iii)	85,96	266.100(c)(2)(i)	266.100(c)(2)(i)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
 Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
heating value of 5,000 Btu/lb or more and considered burned as fuel; reduction of the heating value to below 5,000 Btu/lb by bona fide treatment; blending for dilution to meet the 5,000 Btu/lb limit is prohibited; retention of documentation in records required by 266.100(c)(1)(iii)	85,96	266.100(c)(2)(ii)	266.100(c)(2)(ii)	X			
requirements for exemption from 266.102 through 266.111 for owner or operator of certain metal recovery furnaces; written notice to director; 266.100(c)(1) compliance	96	266.100(c)(3)	266.100(c)(3)	X			
exemption from 266.100(c)(1) requirements for hazardous wastes listed in Appendices XI and XII, Part 266, and baghouse bags used to capture metallic dusts emitted by steel manufacturing, provided:	96	266.100(c)(3)(i)	266.100(c)(3)(i)	X			
waste contains recoverable levels of specified metals	96	266.100(c)(3)(i)(A)	266.100(c)(3)(i)(A)	X			
waste does not exhibit the Toxicity Characteristic of 261.24 for an organic constituent	96	266.100(c)(3)(i)(B)	266.100(c)(3)(i)(B)	X			

**US EPA ARCHIVE DOCUMENT**

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
waste is not a hazardous waste listed in Part 261 Subpart D because it is listed for an organic constituent as identified in Appendix VII of Part 261	96	266.100(c)(3)(i)(C)	266.100(c)(3)(i)(C)	X			
certification by owner or operator under 266.100(c)(3) regarding hazardous waste; sampling and analysis or other information to assure compliance; sampling and analysis conducted according to 266.100(c)(1)(ii); maintain records to document compliance with (c)(3) for at least three years	96	266.100(c)(3)(i)(D)	266.100(c)(3)(i)(D)	X			
basis for case-by-case decisions regarding toxic organic constituents; metal recovery furnace subject to Subpart H requirements after adequate notice and opportunity for comment; factors Director will consider:	96	266.100(c)(3)(ii)	266.100(c)(3)(ii)	X			
concentration and toxicity of organic constituents in the material	96	266.100(c)(3)(ii)(A)	266.100(c)(3)(ii)(A)	X			
level of destruction of toxic constituents provided by the furnace	96	266.100(c)(3)(ii)(B)	266.100(c)(3)(ii)(B)	X			
acceptable ambient levels established in Appendices IV or V, Part 266, exceeded for any toxic organic compound that may be emitted based on certain conditions	96	266.100(c)(3)(ii)(C)	266.100(c)(3)(ii)(C)	X			

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
266.111 direct transfer operation standards apply only to facilities subject to 266.102 or 266.103 standards	85	266.100(d)	266.100(d)	X			
266.112 residue management standards apply to any boiler or industrial furnace burning hazardous waste	85	266.100(e)	266.100(e)	X			
conditional exemption from Subpart H requirements for owners or operators of certain smelting, melting, and refining furnaces, except for 266.112; to be exempt from 266.101 through 266.111, an owner or operator must:	96,111	266.100(f)	266.100(f)	X			
provide a one-time written notice indicating:	96	266.100(f)(1)	266.100(f)(1)	X			
owner or operator claims 266.100(f) exemption	96	266.100(f)(1)(i)	266.100(f)(1)(i)	X			
hazardous waste is burned for legitimate recovery of precious metal	96	266.100(f)(1)(ii)	266.100(f)(1)(ii)	X			
compliance with 266.100(f) sampling and analysis and recordkeeping requirements	96	266.100(f)(1)(iii)	266.100(f)(1)(iii)	X			
sample and analyze hazardous waste as necessary using specified procedures.	96	266.100(f)(2)	266.100(f)(2)	X			
maintain specified records at facility for at least three years	96	266.100(f)(3)	266.100(f)(3)	X			

MANAGEMENT PRIOR TO BURNING

US EPA ARCHIVE DOCUMENT

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
 Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
generators of hazardous waste that is burned in a boiler or industrial furnace subject to Part 262	85	266.101(a)	266.101(a)	X			
transporters of hazardous waste that is burned in a boiler or industrial furnace subject to Part 263	85	266.101(b)	266.101(b)	X			
owners and operators of facilities that store hazardous waste burned in a boiler or industrial furnace subject to the applicable provisions of parts 264, 265, and 270, except as provided by 266.101(c)(2); standards applicable to storage by burners and intermediary facilities	85,111	266.101(c)(1)	266.101(c)(1)	X			
generators of hazardous waste who burn on-site in boilers or industrial furnaces exempt from regulation under 266.108 small quantity burner provisions are exempt from the regulations of parts 264, 265, and 270 applicable to storage units for those storage units that store mixtures of hazardous waste and the primary fuel in tanks that feed mixture directly to burner; hazardous waste storage prior to mixing subject to 266.101(c)(1) regulation	85,111	266.101(c)(2)	266.101(c)(2)	X			

**US EPA ARCHIVE DOCUMENT**

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
<b>PERMIT STANDARDS FOR BURNERS</b>							
owners and operators not operating under interim status and not exempt under 266.108 small quantity burner exemption are subject to 266.102, 270.22 and 270.66 requirements	85	266.102(a)(1)	266.102(a)(1)	X			
		266.102(a)(2)	266.102(a)(2)	X			
		266.102(a)(2)(i)	266.102(a)(2)(i)	X			
		266.102(a)(2)(ii)	266.102(a)(2)(ii)	X			
		266.102(a)(2)(iii)	266.102(a)(2)(iii)	X			
		266.102(a)(2)(iv)	266.102(a)(2)(iv)	X			
		266.102(a)(2)(v)	266.102(a)(2)(v)	X			
		266.102(a)(2)(vi)	266.102(a)(2)(vi)	X			
		266.102(a)(2)(vii)	266.102(a)(2)(vii)	X			
		266.102(a)(2)(viii)	266.102(a)(2)(viii)	X			
applicable 264 provisions	85	266.102(a)(2)(ix)	266.102(a)(2)(ix)	X			

US EPA ARCHIVE DOCUMENT

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
analysis to quantify concentration of any 261, Appendix VIII constituent at levels detectable by specified analytical procedures, alternative methods or best available method; identification; explanation of constituents excluded from analysis; analysis provides 266 Subpart H, 270.22 and 270.66 information to prescribe permit conditions; analysis included in Part B permit application or in trial burn plan for interim status facilities; owners/operators of units not operating under interim status include 270.22 or 270.66(c) information in Part B application, to extent possible	85, 94,96	266.102(b)(1)	266.102(b)(1)	X			
sampling and analysis throughout normal operation to ensure permit-specified physical and chemical composition limits are met	85	266.102(b)(2)	266.102(b)(2)	X			
compliance with 266.104 through 266.107 emissions standards	85	266.102(c)	266.102(c)	X			
burn only hazardous wastes specified in permit under 266.102(e) operating conditions; exception for approved trial burns under 270.66 conditions	85	266.102(d)(1)	266.102(d)(1)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
new permit or permit modification necessary to burn hazardous waste not specified in permit; trial burn results or Part B alternative data form basis for new waste operating requirements	85	266.102(d)(2)	266.102(d)(2)	X			
266.103 interim status boilers and industrial furnaces permitted under 270.66(g) procedures	85	266.102(d)(3)	266.102(d)(3)	X			
permit for new boiler or industrial furnace must establish appropriate conditions for each applicable 266.102 requirement in order to comply with specified standards:	85	266.102(d)(4)	266.102(d)(4)	X			
for period beginning with initial introduction of hazardous waste and ending with initiation of trial burn; such period not to exceed 720 hours; operating requirements in compliance with 266.104-266.107 emissions standards; applicable provisions when seeking waiver from a trial burn; extension for up to 720 additional hours by Director based on good cause demonstration	85	266.102(d)(4)(i)	266.102(d)(4)(i)	X			
during trial burn, operating requirements sufficient for 266.104-266.107 emissions compliance and in accordance with approved trial burn plan	85	266.102(d)(4)(ii)	266.102(d)(4)(ii)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
immediately after trial burn, for minimum period needed to allow sample analysis, data computation, submission and review of trial burn results, and permit modification, operating requirements to ensure 266.104-266.107 emissions compliance	85	266.102(d)(4)(iii)	266.102(d)(4)(iii)	X			
8 for duration of permit, operating requirements based on trial burn or 270.22 alternative data, sufficient to ensure 266.104-266.107 emissions compliance	85,94	266.102(d)(4)(iv)	266.102(d)(4)(iv)	X			
operating requirements specified in the permit apply at all times where hazardous waste is in unit	85	266.102(e)(1)	266.102(e)(1)	X			
operating conditions, either case-by-case for each hazardous waste to ensure compliance with 266.104(a) DRE performance standard or special operating requirements provided by 266.104(a)(4) DRE trial burn waiver; when no waiver, each set of operating requirements will specify composition of hazardous waste to which they apply; permit-specified operating limits for each hazardous waste include:	85	266.102(e)(2)(i)	266.102(e)(2)(i)	X			
feed rate of hazardous waste and other fuels as per 266.102(e)(6)	85	266.102(e)(2)(i)(A)	266.102(e)(2)(i)(A)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
minimum and maximum device production rate when producing normal product as per 266.102(e)(6)	85	266.102(e)(2)(i)(B)	266.102(e)(2)(i)(B)				
		266.102(e)(2)(i)(C)	266.102(e)(2)(i)(C)	X			
allowable variation in boiler and industrial furnace system design or operating procedures	85	266.102(e)(2)(i)(D)	266.102(e)(2)(i)(D)	X			
minimum combustion gas temperature measured at a location indicative of combustion chamber temperature as per 266.102(e)(6)	85	266.102(e)(2)(i)(E)	266.102(e)(2)(i)(E)	X			
appropriate indicator of combustion gas velocity as per 266.102(e)(6), unless 270.66 documentation	85	266.102(e)(2)(i)(F)	266.102(e)(2)(i)(F)	X			
other operating requirements to ensure 266.104(a) DRE compliance	85	266.102(e)(2)(i)(G)	266.102(e)(2)(i)(G)	X			
permit must incorporate carbon monoxide (CO) limit and, as appropriate, hydrocarbon (HC) limit as per 266.104(b)-(f); permit limits specified:	85	266.102(e)(2)(ii)	266.102(e)(2)(ii)	X			
when complying with 266.104(b)(1) CO standard, permit limit is 100 ppmv	85	266.102(e)(2)(ii)(A)	266.102(e)(2)(ii)(A)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
when complying with 266.104(c) alternative CO standard, permit limit based on trial burn, established as specified average, and permit limit for HC is 20 ppmv, except as 266.104(f) provides .	85	266.102(e)(2)(ii)(B)	266.102(e)(2)(ii)(B)	X			
when complying with 266.104(f) alternative HC limit, permit limit for HC and CO is baseline level when hazardous waste is not burned	85	266.102(e)(2)(ii)(C)	266.102(e)(2)(ii)(C)	X			
no hazardous waste as feed during start-up and shut-down, unless device is operating within permit conditions; exception	85	266.102(e)(2)(iii)	266.102(e)(2)(iii)	X			
except as provided in 266.102(e)(3)(ii) and (iii), operating requirements the permit will specify to ensure 266.105 particulate standard compliance:	85	266.102(e)(3)(i)	266.102(e)(3)(i)	X			
total ash feed rate from hazardous waste, other fuels, and industrial furnace feedstocks, as per 266.102(e)(6)	85	266.102(e)(3)(i)(A)	266.102(e)(3)(i)(A)	X			
maximum device production rate when producing normal product as per 266.102(e)(6)	85	266.102(e)(3)(i)(B)	266.102(e)(3)(i)(B)	X			
operation and maintenance controls for hazardous waste firing system and air pollution control system	85	266.102(e)(3)(i)(C)	266.102(e)(3)(i)(C)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
allowable variation in system design including air pollution control system or operating procedures	85	266.102(e)(3)(i)(D)	266.102(e)(3)(i)(D)	X			
9 other operating requirements to ensure 266.111(b) particulate standard compliance	85	266.102(e)(3)(i)(E)	266.102(e)(3)(i)(E)	X			
no permit conditions to ensure particulate standard compliance for 266.105(b) exempt facilities	85	266.102(e)(3)(ii)	266.102(e)(3)(ii)	X			
for cement kilns and light-weight aggregate kilns, permit conditions shall not limit ash content of hazardous waste or other feed materials	85	266.102(e)(3)(iii)	266.102(e)(3)(iii)	X			
operating requirements the permit will specify to conform with 266.106(b) or (e) Tier I or adjusted Tier I metals feed rate screening limits:	85	266.102(e)(4)(i)	266.102(e)(4)(i)	X			
total feed rate of each metal in hazardous waste, other fuels, and industrial furnace feedstocks as per 266.102(e)(6)	85	266.102(e)(4)(i)(A)	266.102(e)(4)(i)(A)	X			
total feed rate of hazardous waste as per 266.102(e)(6)	85	266.102(e)(4)(i)(B)	266.102(e)(4)(i)(B)	X			
sampling and metals analysis program	85,94	266.102(e)(4)(i)(C)	266.102(e)(4)(i)(C)	X			
operating requirements the permit will specify to conform with 266.106(c) Tier II metals emission rate screening limits and 266.106(d) Tier III metals controls:	85	266.102(e)(4)(ii)	266.102(e)(4)(ii)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
maximum emission rate for each metal based on average rate during trial burn	85	266.102(e)(4)(ii)(A)	266.102(e)(4)(ii)(A)	X			
feed rate of total and pumpable hazardous waste as per 266.102(e)(6)(i)	85	266.102(e)(4)(ii)(B)	266.102(e)(4)(ii)(B)	X			
feed rate of each metal in specified feedstreams, measured and specified as per 266.102(e)(6)	85	266.102(e)(4)(ii)(C)	266.102(e)(4)(ii)(C)	X			
	85,96	266.102(e)(4)(ii)(C)(1)	266.102(e)(4)(ii)(C)(1)	X			
		266.102(e)(4)(ii)(C)(2)	266.102(e)(4)(ii)(C)(2)	X			
		266.102(e)(4)(ii)(C)(3)	266.102(e)(4)(ii)(C)(3)	X			
total feed rate of chlorine and chloride in total feedstreams as per 266.102(e)(6)	85	266.102(e)(4)(ii)(D)	266.102(e)(4)(ii)(D)	X			
maximum combustion gas temperature measured at location indicative of combustion chamber temperature as per 266.102(e)(6)	85	266.102(e)(4)(ii)(E)	266.102(e)(4)(ii)(E)	X			
maximum flue gas temperature at inlet to particulate matter air pollution control system as per 266.102(e)(6)	85	266.102(e)(4)(ii)(F)	266.102(e)(4)(ii)(F)	X			
maximum device production rate when producing normal product as per 266.102(e)(6)	85	266.102(e)(4)(ii)(G)	266.102(e)(4)(ii)(G)	X			
operation and maintenance controls of hazardous waste firing system and any air pollution control system	85	266.102(e)(4)(ii)(H)	266.102(e)(4)(ii)(H)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
allowable variation in system design including air pollution control system or operating procedures	85	266.102(e)(4)(ii)(I)	266.102(e)(4)(ii)(I)	X			
other operating requirements to ensure 266.106(c) or (d) metals standards compliance	85	266.102(e)(4)(ii)(J)	266.102(e)(4)(ii)(J)	X			
operating requirements the permit will specify to conform with 266.106(f) alternative implementation approach:	85	266.102(e)(4)(iii)	266.102(e)(4)(iii)	X			
maximum emission rate for each metal based on average rate	85	266.102(e)(4)(iii)(A)	266.102(e)(4)(iii)(A)	X			
feed rate of total and pumpable hazardous waste as per 266.102(e)(6)(i)	85	266.102(e)(4)(iii)(B)	266.102(e)(4)(iii)(B)	X			
10, 11 feed rate of each metal in specified feedstreams, measured and specified as per 266.102(e)(6)	85	266.102(e)(4)(iii)(C)	266.102(e)(4)(iii)(C)	X			
	85,96	266.102(e)(4)(iii)(C)(1)	266.102(e)(4)(iii)(C)(1)	X			
		266.102(e)(4)(iii)(C)(2)	266.102(e)(4)(iii)(C)(2)	X			
total feed rate of chlorine and chloride in total feedstreams as per 266.102(e)(6)	85	266.102(e)(4)(iii)(D)	266.102(e)(4)(iii)(D)	X			
maximum combustion gas temperature measured at location indicative of combustion chamber temperature as per 266.102(e)(6)	85	266.102(e)(4)(iii)(E)	266.102(e)(4)(iii)(E)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
maximum flue gas temperature at inlet to particulate matter air pollution control system as per 266.102(e)(6)	85	266.102(e)(4)(iii)(F)	266.102(e)(4)(iii)(F)	X			
maximum device production rate when producing normal product as per 266.102(e)(6)	85	266.102(e)(4)(iii)(G)	266.102(e)(4)(iii)(G)	X			
operation and maintenance controls of hazardous waste firing system and any air pollution control system	85	266.102(e)(4)(iii)(H)	266.102(e)(4)(iii)(H)	X			
allowable variation in system design including air pollution control system or operating procedures	85	266.102(e)(4)(iii)(I)	266.102(e)(4)(iii)(I)	X			
other operating requirements to ensure 266.106(c) or (d) metals standards compliance	85	266.102(e)(4)(iii)(J)	266.102(e)(4)(iii)(J)	X			
operating requirements the permit will specify to ensure 266.107(b)(1) Tier I total chloride and chlorine feed rate screening limits conformance:	85	266.102(e)(5)(i)	266.102(e)(5)(i)	X			
feed rate of total chloride and chlorine in hazardous waste, other fuels, and industrial furnace feedstocks as per 266.102(e)(6)	85	266.102(e)(5)(i)(A)	266.102(e)(5)(i)(A)	X			
feed rate of total hazardous waste as per 266.102(e)(6)	85	266.102(e)(5)(i)(B)	266.102(e)(5)(i)(B)	X			
sampling and analysis program for total chloride and chlorine	85	266.102(e)(5)(i)(C)	266.102(e)(5)(i)(C)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
operating requirements the permit will specify for 266.107(b)(2) Tier II and 266.107(c) Tier III HCl and Cl <sub>2</sub> emission rate screening limits conformance:	85	266.102(e)(5)(ii)	266.102(e)(5)(ii)	X			
maximum emission rate for HCl and Cl <sub>2</sub> based on average rate	85	266.102(e)(5)(ii)(A)	266.102(e)(5)(ii)(A)	X			
feed rate of total hazardous waste as per 266.102(e)(6)	85	266.102(e)(5)(ii)(B)	266.102(e)(5)(ii)(B)	X			
total feed rate of chlorine and chloride in total feedstreams as per 266.102(e)(6)	85	266.102(e)(5)(ii)(C)	266.102(e)(5)(ii)(C)	X			
maximum device production rate when producing normal product as per 266.102(e)(6)	85	266.102(e)(5)(ii)(D)	266.102(e)(5)(ii)(D)	X			
operation and maintenance controls of hazardous waste firing system and any air pollution control system	85	266.102(e)(5)(ii)(E)	266.102(e)(5)(ii)(E)	X			
allowable variation in system design including air pollution control system or operating procedures	85	266.102(e)(5)(ii)(F)	266.102(e)(5)(ii)(F)	X			
other operating requirements to ensure 266.107(b)(2) or (c) HCl or Cl <sub>2</sub> standards compliance	85	266.102(e)(5)(ii)(G)	266.102(e)(5)(ii)(G)	X			
measuring parameters and establishing limits based on trial burn data	85,94	266.102(e)(6)	266.102(e)(6)	X			

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
as specified in 266.102(e)(2)-(5), each operating parameter shall be measured and permit limits on the parameter established according to either of following procedures:	85	266.102(e)(6)(i)	266.102(e)(6)(i)	X			
measured and recorded on instantaneous basis and permit limit based on time-weighted average	85	266.102(e)(6)(i)(A)	266.102(e)(6)(i)(A)	X			
hourly rolling average basis as defined	85	266.102(e)(6)(i)(B)(1)	266.102(e)(6)(i)(B)(1)	X			
		266.102(e)(6)(i)(B)(1)(i)	266.102(e)(6)(i)(B)(1)(i)	X			
	85,94	266.102(e)(6)(i)(B)(1)(ii)	266.102(e)(6)(i)(B)(1)(ii)	X			
12 permit limit based on average over all valid test runs of highest hourly rolling average value per run	85,94	266.102(e)(6)(i)(B)(2)	266.102(e)(6)(i)(B)(2)	X			
feed rate limits for carcinogenic metals and lead established on either an hourly rolling average basis or on (up to) to 24-hour rolling average basis; requirements for 2- to 24-hour average period:	85,94	266.102(e)(6)(ii)	266.102(e)(6)(ii)	X			
feed rate of each metal limited to ten times the allowable hourly rolling average basis feed rate	85	266.102(e)(6)(ii)(A)	266.102(e)(6)(ii)(A)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
12  specifications the continuous monitor shall meet	85	266.102(e)(6)(ii)(B)	266.102(e)(6)(ii)(B)	X			
		266.102(e)(6)(ii)(B)(1)	266.102(e)(6)(ii)(B)(1)	X			
	85,94	266.102(e)(6)(ii)(B)(2)	266.102(e)(6)(ii)(B)(2)	X			
feed rate permit limit based on specified average	85	266.102(e)(6)(ii)(C)	266.102(e)(6)(ii)(C)	X			
feed rate limits for metals, total chloride and chlorine, and ash established and monitored based on feedstream concentration and flow rate; flow rate continuously monitored as per 266.102(e)(6)(i) and (ii)	85	266.102(e)(6)(iii)	266.102(e)(6)(iii)	X			
if no simultaneous demonstration of 266.104-266.107 compliance during a set of test runs, operating conditions of additional test runs as close as possible to original operating conditions	85	266.102(e)(6)(iv)(A)	266.102(e)(6)(iv)(A)	X			
facility to operate under trial burn conditions and reach steady-state operations before obtaining test data to demonstrate 266.104-266.107 emissions standards compliance or establishing operating parameter limits; specific industrial furnaces need not reach steady-state conditions for flow of metals prior to beginning metals emissions compliance testing	85,94	266.102(e)(6)(iv)(B)	266.102(e)(6)(iv)(B)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
trial burn data obtained during emissions sampling are used to establish operating parameter limits in the permit when parameter must be established as per 266.102(e)	85	266.102(e)(6)(iv)(C)	266.102(e)(6)(iv)(C)	X			
requirements for controlling fugitive emissions	85	266.102(e)(7)(i)	266.102(e)(7)(i)	X			
		266.102(e)(7)(i)(A)	266.102(e)(7)(i)(A)	X			
		266.102(e)(7)(i)(B)	266.102(e)(7)(i)(B)	X			
		266.102(e)(7)(i)(C)	266.102(e)(7)(i)(C)	X			
automatic waste feed cutoff required; Director may limit number of cutoffs per operating period; additional requirements include:	85	266.102(e)(7)(ii)	266.102(e)(7)(ii)	X			
maintenance of permit limit for minimum combustion chamber temperature while hazardous waste or residues remain in chamber	85	266.102(e)(7)(ii)(A)	266.102(e)(7)(ii)(A)	X			
exhaust gases ducted to air pollution control system while hazardous waste or residues remain in chamber	85	266.102(e)(7)(ii)(B)	266.102(e)(7)(ii)(B)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOGOUS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
continued monitoring of parameters with limits during cutoff and hazardous waste feed not restarted until parameters comply with limits; for parameters monitored on instantaneous basis, conditions for restarting hazardous waste feed	85	266.102(e)(7)(ii)(C)	266.102(e)(7)(ii)(C)	X			
cease burning hazardous waste when changes in combustion properties, feed rates, or design or operating conditions deviate from permit limits	85	266.102(e)(7)(iii)	266.102(e)(7)(iii)	X			
owner or operator, while burning hazardous waste, must monitor and record:	85	266.102(e)(8)(i)	266.102(e)(8)(i)	X			
specified feed rates and composition of specified materials	85	266.102(e)(8)(i)(A)	266.102(e)(8)(i)(A)	X			
CO, HC, and oxygen on a continuous basis as specified; monitors installed, operated and maintained as per 266, Appendix IX methods	85	266.102(e)(8)(i)(B)	266.102(e)(8)(i)(B)	X			
sampling and analysis as requested to verify that requirements established in permit achieve 266.104-266.107 standards	85	266.102(e)(8)(i)(C)	266.102(e)(8)(i)(C)	X			
monitors record data in permit limit units, unless permit allows otherwise	85	266.102(e)(8)(ii)	266.102(e)(8)(ii)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
daily visual inspection of boiler or industrial furnace and associated equipment when they contain hazardous waste	85	266.102(e)(8)(iii)	266.102(e)(8)(iii)	X			
test automatic feed cutoff system and associated alarms at least once every 7 days when hazardous waste is burned unless specified conditions are demonstrated; operational testing at least once every 30 days	85	266.102(e)(8)(iv)	266.102(e)(8)(iv)	X			
monitoring and inspection data recorded and placed in 264.73 operating record	85	266.102(e)(8)(v)	266.102(e)(8)(v)	X			
compliance with 266.111 if direct transfer of hazardous waste to boiler or industrial furnace without use of storage unit	85	266.102(e)(9)	266.102(e)(9)	X			
all 266.102-required information and data in facility operating record until closure of the facility	85,96	266.102(e)(10)	266.102(e)(10)	X			
remove all hazardous waste and hazardous waste residues at closure	85	266.102(e)(11)	266.102(e)(11)	X			
<b>INTERIM STATUS STANDARDS FOR BURNERS</b>							
establish minimum national standards for owners and operators of existing boilers and industrial furnaces until permitted under 266.102(d) or closed	85	266.103(a)(1)(i)	266.103(a)(1)(i)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
definition of "existing or in existence"; facility has commenced construction if all permits necessary to begin physical construction are obtained and either:	85,94	266.103(a)(1)(ii)	266.103(a)(1)(ii)	X			
continuous on-site, physical construction program has begun	85	266.103(a)(1)(ii)(A)	266.103(a)(1)(ii)(A)	X			
contractual obligations cannot be cancelled or modified without substantial loss and physical construction is to be completed within reasonable time	85	266.103(a)(1)(ii)(B)	266.103(a)(1)(ii)(B)	X			
if boiler or industrial furnace at facility with permit or interim status, then compliance with 270.42 permit modification or 270.72 interim status changes	85	266.103(a)(1)(iii)	266.103(a)(1)(iii)	X			
266.103 requirements not applicable to hazardous waste and facilities exempt under 266.100(b) or 266.108	85	266.103(a)(2)	266.103(a)(2)	X			
F020-F023, F026 or F027 hazardous waste listed for dioxin and hazardous waste derived from these wastes may not be burned in interim status boiler or industrial furnace	85,96	266.103(a)(3)	266.103(a)(3)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIV-ALENT	LESS STRIN-GENT	MORE STRIN-GENT	BROADE R IN SCOPE
interim status owners and operators subject to specified 265 provisions:	85	266.103(a)(4)	266.103(a)(4)	X			
		266.103(a)(4)(i)	266.103(a)(4)(i)	X			
		266.103(a)(4)(ii)	266.103(a)(4)(ii)	X			
		266.103(a)(4)(iii)	266.103(a)(4)(iii)	X			
		266.103(a)(4)(iv)	266.103(a)(4)(iv)	X			
		266.103(a)(4)(v)	266.103(a)(4)(v)	X			
		266.103(a)(4)(vi)	266.103(a)(4)(vi)	X			
		266.103(a)(4)(vii)	266.103(a)(4)(vii)	X			
		266.103(a)(4)(viii)	266.103(a)(4)(viii)	X			
controls that apply to interim status industrial furnaces that feed hazardous waste for a purpose other than solely as an ingredient at any location other than the hot end or where fuels are normally fired:	85,96	266.103(a)(5)	266.103(a)(5)	X			
fed at location where temperatures are at least 1800° F	85	266.103(a)(5)(i)(A)	266.103(a)(5)(i)(A)	X			
determination and documentation in facility record of adequate oxygen	85	266.103(a)(5)(i)(B)	266.103(a)(5)(i)(B)	X			
for cement kiln systems, hazardous waste fed into kiln	85	266.103(a)(5)(i)(C)	266.103(a)(5)(i)(C)	X			

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
applicability of 266.104(c) or 266.103(c)(5) hydrocarbon controls	85,96	266.103(a)(5)(i)(D)	266.103(a)(5)(i)(D)	X			
criteria for burning hazardous waste for a purpose other than solely as an ingredient:	85	266.103(a)(5)(ii)	266.103(a)(5)(ii)	X			
total concentration of 261; Appendix VIII nonmetal compounds exceed 500 ppm by weight as fired and considered burned for destruction; reduction of the concentration of nonmetal compounds to the 500 ppm limit by bona fide treatment; blending for dilution to meet the 500 ppm limit prohibited; retention of documentation in facility record	85,96	266.103(a)(5)(ii)(A)	266.103(a)(5)(ii)(A)	X			
heating value of 5,000 Btu/lb or more, as fired, and considered burned as fuel; reduction of the heating value of a waste as-generated to below 5,000 Btu/lb limit by bona fide treatment; blending to augment heating value to meet the 5,000 Btu/lb limit prohibited; retention of documentation in facility record	85,96	266.103(a)(5)(ii)(B)	266.103(a)(5)(ii)(B)	X			
burning hazardous waste with heating value less than 5,000 Btu/lb prohibited; situation where 5,000 Btu/lb limit can be exceeded; exceptions:	85,96	266.103(a)(6)	266.103(a)(6)	X			

US EPA ARCHIVE DOCUMENT

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
hazardous waste burned solely as an ingredient	96	266.103(a)(6)(i)	266.103(a)(6)(i)	X			
hazardous waste burned for purposes of compliance testing for a total period of time not to exceed 720 hours	96	266.103(a)(6)(ii)	266.103(a)(6)(ii)	X			
waste burned if Director has documentation to show that, prior to August 21, 1991:	96	266.103(a)(6)(iii)	266.103(a)(6)(iii)	X			
boiler or industrial furnace operating under Part 265, Subpart O or P requirements	96	266.103(a)(6)(iii)(A)	266.103(a)(6)(iii)(A)	X			
boiler or industrial furnace met 270.70 interim status eligibility requirements for Part 265, Subpart O or Subpart P	96	266.103(a)(6)(iii)(B)	266.103(a)(6)(iii)(B)	X			
hazardous waste with a heating value less than 5,000 Btu/lb burned prior to August 21, 1991	96	266.103(a)(6)(iii)(C)	266.103(a)(6)(iii)(C)	X			
such waste burned in halogen acid furnace if waste burned as an excluded ingredient under 261.2(e) prior to February 21, 1991 and documentation kept on file	96	266.103(a)(6)(iv)	266.103(a)(6)(iv)	X			
266.111 compliance if hazardous waste directly transferred from transport vehicle to boiler or industrial furnace without storage unit use	85	266.103(a)(7)	266.103(a)(7)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
August 21, 1991 submittal date for 266.103(b)(2) information; establish limits for 266.103(b)(3) parameters; certificate of precompliance; burning limited to 266.103(b)(3) conditions until 266.103(b)(8) revised certification of precompliance, or 266.103(c) certification of compliance, or permit is issued	85	266.103(b)(1)	266.103(b)(1)	X			
information to be submitted with certification of precompliance to support determination and compliance with operating parameter limits	85	266.103(b)(2)	266.103(b)(2)	X			
general facility information	85	266.103(b)(2)(i)	266.103(b)(2)(i)	X			
		266.103(b)(2)(i)(A)	266.103(b)(2)(i)(A)	X			
		266.103(b)(2)(i)(B)	266.103(b)(2)(i)(B)	X			
		266.103(b)(2)(i)(C)	266.103(b)(2)(i)(C)	X			
		266.103(b)(2)(i)(D)	266.103(b)(2)(i)(D)	X			
		266.103(b)(2)(i)(E)	266.103(b)(2)(i)(E)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
except for facilities complying with Tier I or Adjusted Tier I feed rate screening limits provided by 266.106(b) or (e) and 266.107(b)(1) or (e), estimated uncontrolled emissions of particulate matter, each 266.106 metal, hydrogen chloride and chlorine, and following information to support determinations:	85,111	266.103(b)(2)(ii)	266.103(b)(2)(ii)	X			
feed rate of specified materials in each feedstream	85,94	266.103(b)(2)(ii)(A)	266.103(b)(2)(ii)(A)	X			
estimated partitioning factor to combustion gas for 266.103(b)(2)(ii)(A) materials, basis for estimate, and estimate of partitioning to HCl and Cl <sub>2</sub> of total chloride and chlorine in feed materials; use best engineering judgment or 266, Appendix IX procedures	85,94	266.103(b)(2)(ii)(B)	266.103(b)(2)(ii)(B)	X			
for industrial furnaces that recycle collected particulate matter and certify compliance with 266.103(c)(ii)(A) metals emissions standards, estimated enrichment factor for each metal, using best engineering judgment or specified 266, Appendix IX procedures	85	266.103(b)(2)(ii)(C)	266.103(b)(2)(ii)(C)	X			
basis for best engineering judgment; 270.11(d) certification of determinations included in certification of precompliance	85,94	266.103(b)(2)(ii)(D)	266.103(b)(2)(ii)(D)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
for facilities complying with Tier I or Adjusted Tier I feed rate screening limits, the feed rate of specified materials in each feed stream	85,111	266.103(b)(2)(iii)	266.103(b)(2)(iii)	X			
for facilities complying with Tier II or III emission limits for metals or HCl or Cl <sub>2</sub> , estimated controlled emissions rates of particulate matter, each 266.106 metal, HCl and Cl <sub>2</sub> , and following information to support determinations:	85,94	266.103(b)(2)(iv)	266.103(b)(2)(iv)	X			
estimated air pollution control system (APCS) removal efficiency for specified materials	85	266.103(b)(2)(iv)(A)	266.103(b)(2)(iv)(A)	X			
use best engineering judgment or 266, Appendix IX procedures	85	266.103(b)(2)(iv)(B)	266.103(b)(2)(iv)(B)	X			
basis for best engineering judgment in conformance with 266.103(b)(2)(ii)(D)	85	266.103(b)(2)(iv)(C)	266.103(b)(2)(iv)(C)	X			
determination of allowable emissions rates for specified materials and information to support such determinations to include:	85	266.103(b)(2)(v)	266.103(b)(2)(v)	X			

US EPA ARCHIVE DOCUMENT

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
	85	266.103(b)(2)(v)(A)	266.103(b)(2)(v)(A)	X			
		266.103(b)(2)(v)(A)(1)	266.103(b)(2)(v)(A)(1)	X			
		266.103(b)(2)(v)(A)(2)	266.103(b)(2)(v)(A)(2)	X			
		266.103(b)(2)(v)(A)(3)	266.103(b)(2)(v)(A)(3)	X			
		266.103(b)(2)(v)(A)(4)	266.103(b)(2)(v)(A)(4)	X			
	85,94	266.103(b)(2)(v)(A)(5)	266.103(b)(2)(v)(A)(5)	X			
	85	266.103(b)(2)(v)(A)(6)	266.103(b)(2)(v)(A)(6)	X			
266.103(b)(2)(v)(A)(7)		266.103(b)(2)(v)(A)(7)	X				
for all facilities:	85						
for owners or operators using Tier III site specific dispersion modeling to determine 266.106(d) or 266.107(c) allowable levels, or adjusted Tier I feed rate screening limits under 266.106(e) or 266.107(e):	85	266.103(b)(2)(v)(B)	266.103(b)(2)(v)(B)	X			
		266.103(b)(2)(v)(B)(1)	266.103(b)(2)(v)(B)(1)	X			
		266.103(b)(2)(v)(B)(2)	266.103(b)(2)(v)(B)(2)	X			
		266.103(b)(2)(v)(B)(3)	266.103(b)(2)(v)(B)(3)	X			
		266.103(b)(2)(v)(B)(4)	266.103(b)(2)(v)(B)(4)	X			
for facilities complying with Tier II or III emissions rate controls for metals or HCl and Cl <sub>2</sub> , comparison of 266.103(b)(2)(iv) estimated rates with 266.103(b)(2)(v) allowable rates	85,94	266.103(b)(2)(vi)	266.103(b)(2)(vi)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
for facilities complying with Tier I or adjusted Tier I feed rate screening limits for metals or total chloride and chlorine, comparison of actual feed rates determined under 266.103(b)(2)(iii) to Tier I allowable feed rates	85	266.103(b)(2)(vii)	266.103(b)(2)(vii)	X			
for industrial furnaces that feed hazardous waste for any purpose other than solely as an ingredient at any location other than product discharge end of device, documentation of 266.103(a)(5)(i)(A)-(C) compliance	85	266.103(b)(2)(viii)	266.103(b)(2)(viii)	X			
for industrial furnaces that recycle collected particulate matter back into the furnace and that will certify 266.103(c)(3)(ii)(A) metals emissions standards compliance, applicable particulate matter standard and precompliance limit on metal concentration	85	266.103(b)(2)(ix)	266.103(b)(2)(ix)	X			
		266.103(b)(2)(ix)(A)	266.103(b)(2)(ix)(A)	X			
		266.103(b)(2)(ix)(B)	266.103(b)(2)(ix)(B)	X			
establish limits on 266.103(b)(3)(i)-(v) parameters consistent with 266.103(b)(2) determinations and certify the facility will operate within the limits during interim status when there is hazardous waste in the unit until certain conditions are met	85	266.103(b)(3)	266.103(b)(3)	X			
feed rate of total hazardous waste and pumpable hazardous waste	85	266.103(b)(3)(i)	266.103(b)(3)(i)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
	85,94	266.103(b)(3)(ii)	266.103(b)(3)(ii)	X			
	85	266.103(b)(3)(ii)(A)	266.103(b)(3)(ii)(A)	X			
	85,111	266.103(b)(3)(ii)(B)	266.103(b)(3)(ii)(B)	X			
feed rate of each metal in specified feedstreams	85	266.103(b)(3)(ii)(C)	266.103(b)(3)(ii)(C)	X			
total feed rate of chlorine and chloride in total feedstreams	85.	266.103(b)(3)(iii)	266.103(b)(3)(iii)	X			
total feed rate of ash in total feedstreams, except ash feed rate for cement kilns and light-weight aggregate kilns is not limited	85	266.103(b)(3)(iv)	266.103(b)(3)(iv)	X			
maximum production rate when producing normal product, unless complying with the Tier I or Adjusted Tier I feed rate screening limits for chlorine under 266.106(b)(1) or (e) and for all metals under 266.106(b) or (e), and uncontrolled particulate emissions do not exceed 266.105 standard	85,111	266.103(b)(3)(v)	266.103(b)(3)(v)	X			
special operating requirements under 266, Appendix IX for furnaces that recycle collected particulate matter back into furnace and that certify compliance with metals emissions controls under 266.103(c)(3)(ii)(A)	85	266.103(b)(4)	266.103(b)(4)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
limits on 266.103(b)(3) parameters established and continuously monitoring under:	85	266.103(b)(5)(i)	266.103(b)(5)(i)	X			
instantaneous limits	85,96	266.103(b)(5)(i)(A)	266.103(b)(5)(i)(A)	X			
hourly rolling average basis as defined	85	266.103(b)(5)(i)(B)	266.103(b)(5)(i)(B)	X			
	85,94	266.103(b)(5)(i)(B)(1)	266.103(b)(5)(i)(B)(1)	X			
		266.103(b)(5)(i)(B)(2)	266.103(b)(5)(i)(B)(2)	X			
	feed rate limits for carcinogenic metals and lead established on either an hourly rolling average basis or on (up to) 24-hour rolling average basis; requirements for 2- to 24-hour average period:	85	266.103(b)(5)(ii)	266.103(b)(5)(ii)	X		
feed rate of each metal limited to ten times the allowable hourly rolling average basis feed rate	85	266.103(b)(5)(ii)(A)	266.103(b)(5)(ii)(A)	X			
specifications the continuous monitor shall meet:	85	266.103(b)(5)(ii)(B)	266.103(b)(5)(ii)(B)	X			
	85,94	266.103(b)(5)(ii)(B)(1)	266.103(b)(5)(ii)(B)(1)	X			
		266.103(b)(5)(ii)(B)(2)	266.103(b)(5)(ii)(B)(2)	X			

12

12

US EPA ARCHIVE DOCUMENT

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
feed rate limits for metals, total chloride and chlorine, and ash established and monitored based on feedstream concentration and flow rate; flow rate continuously monitored as per 266.103(b)(5)(i) and (ii)	85	266.103(b)(5)(iii)	266.103(b)(5)(iii)	X			
on or before August 21, 1991, owner or operator submits notice to major local newspaper and sends copy of notice to State and local government units; provide evidence of notice submittal for publication with certification of pre-compliance to Director; notice must bear specified title and include:	85,94	266.103(b)(6)	266.103(b)(6)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
 Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:				
				EQUIV- ALENT	LESS STRIN- GENT	MORE STRIN- GENT	BROADE R IN SCOPE	
	85	266.103(b)(6)(i)	266.103(b)(6)(i)	X				
		266.103(b)(6)(ii)	266.103(b)(6)(ii)	X				
		266.103(b)(6)(iii)	266.103(b)(6)(iii)	X				
		266.103(b)(6)(iv)	266.103(b)(6)(iv)	X				
		266.103(b)(6)(v)	266.103(b)(6)(v)	X				
		266.103(b)(6)(vi)	266.103(b)(6)(vi)	X				
		266.103(b)(6)(vii)	266.103(b)(6)(vii)	X				
	85,96	266.103(b)(6)(viii)	266.103(b)(6)(viii)	X				
		266.103(b)(6)(viii)(A)	266.103(b)(6)(viii)(A)	X				
		266.103(b)(6)(viii)(B)	266.103(b)(6)(viii)(B)	X				
	information to include in public notice	85	266.103(b)(6)(ix)	266.103(b)(6)(ix)	X			
			266.103(b)(6)(x)	266.103(b)(6)(x)	X			

**US EPA ARCHIVE DOCUMENT**

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
when monitoring systems for 266.103(c)(1)(v)-(xiii) operating parameters are installed and operating in conformance with vendor or 266, Appendix IX specifications, continuous monitoring required and records maintained in operating record	85	266.103(b)(7)	266.103(b)(7)	X			
submittal of revised certification of pre-compliance under 266.103(b)(2)&(3) procedures	85	266.103(b)(8)	266.103(b)(8)	X			
266.103(b)(6) public notice requirements not applicable to recertifications	85	266.103(b)(8)(i)	266.103(b)(8)(i)	X			
operation of facility within limits established for 266.103(b)(3) parameters until 266.103(b) revised certification or 266.103(c) certification of compliance is submitted	85	266.103(b)(8)(ii)	266.103(b)(8)(ii)	X			
language of signed statement that must be included with the certification of precompliance	85	266.103(b)(9)	266.103(b)(9)	X			
conduct emissions testing to document compliance with 266.104(b)-(e), 266.105-266.107 and 266.103(a)(5)(i)(D) emissions standards; submittal of certification of compliance on or before August 21, 1992	85,94	266.103(c)	266.103(c)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
establish limits and all applicable emission standards on 266.103(c)(1) (i)-(xiii) parameters based on operations during compliance test or as otherwise specified and include with certification of compliance; device will be operated within these limits and applicable emission standards of 266.104(b)-(e), 266.105, 266.106, 266.107 and 266.103(a)(5)(i)(D) when hazardous waste is in the unit	85,94,96,111,114	266.103(c)(1)	266.103(c)(1)	X			
13 feed rate of total hazardous waste and pumpable hazardous waste	85	266.103(c)(1)(i)	266.103(c)(1)(i)	X			
13	85	266.103(c)(1)(ii)	266.103(c)(1)(ii)	X			
	85,111	266.103(c)(1)(ii)(A)	266.103(c)(1)(ii)(A)	X			
	111	266.103(c)(1)(ii)(A)(1)	266.103(c)(1)(ii)(A)(1)	X			
		266.103(c)(1)(ii)(A)(2)	266.103(c)(1)(ii)(A)(2)	X			
	85	266.103(c)(1)(ii)(B)	266.103(c)(1)(ii)(B)	X			
	85,111,114	266.103(c)(1)(ii)(C)	266.103(c)(1)(ii)(C)	X			
13 total feed rate of chlorine and chloride in total feed streams; the operating limits for facilities that comply with Tier I or Adjusted Tier I feed rate screening limits	85,111,114	266.103(c)(1)(iii)	266.103(c)(1)(iii)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
13 total feed rate of ash in total feedstreams, except ash feed rate for cement kilns and light-weight aggregate kilns is not limited	85,94	266.103(c)(1)(iv)	266.103(c)(1)(iv)	X			
13 carbon monoxide concentration and, where required, hydrocarbon concentration in stack gas; CO and HC limits	85	266.103(c)(1)(v)	266.103(c)(1)(v)	X			
13 maximum production rate when producing normal product, unless complying with Tier I or Adjusted Tier I feed rate screening limits for chlorine under 266.107(b)(1) or (e) and for all metals under 266.106(b) or (e), and uncontrolled particulate emissions do not exceed 266.105 standard	85, 111,114	266.103(c)(1)(vi)	266.103(c)(1)(vi)	X			
13 maximum combustion chamber temperature with temperature measured where specified; exception	85,114	266.103(c)(1)(vii)	266.103(c)(1)(vii)	X			
13 maximum flue gas temperature entering a particulate matter control device; exception	85,114	266.103(c)(1)(viii)	266.103(c)(1)(viii)	X			
13	85,94	266.103(c)(1)(ix)	266.103(c)(1)(ix)	X			
limits for systems using wet scrubbers, including wet ionizing scrubbers; exception:	85	266.103(c)(1)(ix)(A)	266.103(c)(1)(ix)(A)	X			
		266.103(c)(1)(ix)(B)	266.103(c)(1)(ix)(B)	X			
		266.103(c)(1)(ix)(C)	266.103(c)(1)(ix)(C)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
13 systems using venturi scrubbers, the minimum differential gas pressure across the venturi; exception	85	266.103(c)(1)(x)	266.103(c)(1)(x)	X			
13 limits for systems using dry scrubbers; exception:	85,94,114	266.103(c)(1)(xi)	266.103(c)(1)(xi)	X			
	85	266.103(c)(1)(xi)(A)	266.103(c)(1)(xi)(A)	X -			
	85,114	266.103(c)(1)(xi)(B)	266.103(c)(1)(xi)(B)	X			
13 limits for systems using wet ionizing scrubbers or electrostatic precipitators; exception	85,94	266.103(c)(1)(xii)	266.103(c)(1)(xii)	X			
	85	266.103(c)(1)(xii)(A)	266.103(c)(1)(xii)(A)	X			
13 systems using fabric filters, the minimum pressure drop; exception	85	266.103(c)(1)(xiii)	266.103(c)(1)(xiii)	X			
	85	266.103(c)(2)	266.103(c)(2)	X			
at least 30 days prior to 266.103(c)(3) compliance testing, notify Director and submit required information:		266.103(c)(2)(i)	266.103(c)(2)(i)	X			
		266.103(c)(2)(i)(A)	266.103(c)(2)(i)(A)	X			
		266.103(c)(2)(i)(B)	266.103(c)(2)(i)(B)	X			
		266.103(c)(2)(i)(C)	266.103(c)(2)(i)(C)	X			
	85	266.103(c)(2)(i)(D)	266.103(c)(2)(i)(D)	X			
general facility information	85						

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
		266.103(c)(2)(ii)	266.103(c)(2)(ii)	X			
		266.103(c)(2)(ii)(A)	266.103(c)(2)(ii)(A)	X			
		266.103(c)(2)(ii)(B)	266.103(c)(2)(ii)(B)	X			
		266.103(c)(2)(ii)(C)	266.103(c)(2)(ii)(C)	X			
		266.103(c)(2)(ii)(D)	266.103(c)(2)(ii)(D)	X			
		266.103(c)(2)(ii)(D)(1)	266.103(c)(2)(ii)(D)(1)	X			
		266.103(c)(2)(ii)(D)(2)	266.103(c)(2)(ii)(D)(2)	X			
		266.103(c)(2)(ii)(D)(3)	266.103(c)(2)(ii)(D)(3)	X			
		266.103(c)(2)(ii)(E)	266.103(c)(2)(ii)(E)	X			
specific information on each device to be tested	85	266.103(c)(2)(ii)(F)	266.103(c)(2)(ii)(F)	X			
information on testing planned, including complete copy of test protocol and QA/QC plan, and summary description for each test that provides specified information	85	266.103(c)(2)(iii)	266.103(c)(2)(iii)	X			
		266.103(c)(2)(iii)(A)	266.103(c)(2)(iii)(A)	X			
		266.103(c)(2)(iii)(B)	266.103(c)(2)(iii)(B)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
13 compliance testing under 266.103(b) and 266.103(c)(2) conditions; case by case approval to use compliance test data from one unit in lieu of testing a similar on-site unit; information required to support owner or operator request; approval based on 266.103(c) requirements	85,96	266.103(c)(3)(i)	266.103(c)(3)(i)	X			
13 industrial furnaces that recycle collected particulate matter from air pollution control system must test to determine 266.106(c) or (d) metals standards compliance using one of the following procedures:	85	266.103(c)(3)(ii)	266.103(c)(3)(ii)	X			
13 266, Appendix IX testing requirements in "Alternative Method for Implementing Metals Controls"	85	266.103(c)(3)(ii)(A)	266.103(c)(3)(ii)(A)	X			

**US EPA ARCHIVE DOCUMENT**

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
 Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
13 stack emissions testing for 6 hrs/day while hazardous waste is burned during interim status; conditions for testing; analysis for metals content to assure 266.106(c) or (d) compliance; parameters for which operating limits must be established under 266.103(c)(3)	85	266.103(c)(3)(ii)(B)	266.103(c)(3)(ii)(B)	X			
		266.103(c)(3)(ii)(B)(1)	266.103(c)(3)(ii)(B)(1)	X			
		266.103(c)(3)(ii)(B)(2)	266.103(c)(3)(ii)(B)(2)	X			
		266.103(c)(3)(ii)(B)(3)	266.103(c)(3)(ii)(B)(3)	X			
		266.103(c)(3)(ii)(B)(4)	266.103(c)(3)(ii)(B)(4)	X			
		266.103(c)(3)(ii)(B)(5)	266.103(c)(3)(ii)(B)(5)	X			
13 conduct compliance testing and establish limits on 266.103(c)(1) parameters after kiln system has been conditioned and has reached equilibrium with metals feed and metals emissions; conditions to be met during conditioning	85	266.103(c)(3)(ii)(C)	266.103(c)(3)(ii)(C)	X			
13 if no simultaneous demonstration of 266.104-266.107 compliance during a set of test runs, operating conditions of additional test runs as close as possible to original operating conditions	85	266.103(c)(3)(iii)(A)	266.103(c)(3)(iii)(A)	X			

US EPA ARCHIVE DOCUMENT

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
13 facility to operate under compliance test conditions and reach steady-state operations before obtaining test data to demonstrate 266.104-266.107 emissions standards compliance or establishing operating parameter limits; specific industrial furnaces need not reach steady-state conditions prior to beginning metals compliance testing	85	266.103(c)(3)(iii)(B)	266.103(c)(3)(iii)(B)	X			
13 compliance test data obtained during emissions sampling are used to establish operating parameter limits in the certification of compliance when parameter must be established as per 266.103(c)(1)	85	266.103(c)(3)(iii)(C)	266.103(c)(3)(iii)(C)	X			
within 90 days of completing compliance testing, certification to Director of compliance with 266.104(b),(c)&(e), 266.105-266.107 and 266.103(a)(5)(i)(D) emissions standards; certification must include:	85	266.103(c)(4)	266.103(c)(4)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
	85	266.103(c)(4)(i)	266.103(c)(4)(i)	X			
		266.103(c)(4)(i)(A)	266.103(c)(4)(i)(A)	X			
		266.103(c)(4)(i)(B)	266.103(c)(4)(i)(B)	X			
	85,94	266.103(c)(4)(i)(C)	266.103(c)(4)(i)(C)	X			
	85	266.103(c)(4)(i)(D)	266.103(c)(4)(i)(D)	X			
		266.103(c)(4)(i)(E)	266.103(c)(4)(i)(E)	X			
		266.103(c)(4)(i)(F)	266.103(c)(4)(i)(F)	X			
		266.103(c)(4)(i)(G)	266.103(c)(4)(i)(G)	X			
		266.103(c)(4)(i)(H)	266.103(c)(4)(i)(H)	X			
general facility and testing information		266.103(c)(4)(i)(I)	266.103(c)(4)(i)(I)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
		266.103(c)(4)(ii)	266.103(c)(4)(ii)	X			
		266.103(c)(4)(ii)(A)	266.103(c)(4)(ii)(A)	X			
		266.103(c)(4)(ii)(B)	266.103(c)(4)(ii)(B)	X			
		266.103(c)(4)(ii)(B)(1)	266.103(c)(4)(ii)(B)(1)	X			
		266.103(c)(4)(ii)(B)(2)	266.103(c)(4)(ii)(B)(2)	X			
		266.103(c)(4)(ii)(B)(3)	266.103(c)(4)(ii)(B)(3)	X			
	85	266.103(c)(4)(ii)(B)(4)	266.103(c)(4)(ii)(B)(4)	X			
	85,94	266.103(c)(4)(ii)(B)(5)	266.103(c)(4)(ii)(B)(5)	X			
		266.103(c)(4)(ii)(B)(6)	266.103(c)(4)(ii)(B)(6)	X			
		266.103(c)(4)(ii)(B)(7)	266.103(c)(4)(ii)(B)(7)	X			
		266.103(c)(4)(ii)(B)(8)	266.103(c)(4)(ii)(B)(8)	X			
specific information on each test	85	266.103(c)(4)(ii)(B)(9)	266.103(c)(4)(ii)(B)(9)	X			
comparison of actual emissions per test with emissions limits prescribed by 266.104(b),(c)&(e) and 266.105-266.107 and established in 266.103(b) certification of precompliance	85	266.103(c)(4)(iii)	266.103(c)(4)(iii)	X			
determination of operating limits based on all valid runs for 266.103(c)(1) parameters using one of two procedures:	85	266.103(c)(4)(iv)	266.103(c)(4)(iv)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
instantaneous limits	85	266.103(c)(4)(iv)(A)	266.103(c)(4)(iv)(A)	X			
hourly rolling average basis as defined	85	266.103(c)(4)(iv)(B)(1)	266.103(c)(4)(iv)(B)(1)	X			
		266.103(c)(4)(iv)(B)(1)(i)	266.103(c)(4)(iv)(B)(1)(i)	X			
		266.103(c)(4)(iv)(B)(1)(ii)	266.103(c)(4)(iv)(B)(1)(ii)	X			
parameter operating limit based on compliance test data and specific average	85	266.103(c)(4)(iv)(B)(2)	266.103(c)(4)(iv)(B)(2)	X			
feed rate limits for carcinogenic metals and lead established on either an hourly rolling average basis or on (up to) 24-hour rolling average basis; requirements for 2- to 24-hour average period:	85	266.103(c)(4)(iv)(C)	266.103(c)(4)(iv)(C)	X			
feed rate of each metal limited to ten times the allowable hourly rolling average basis feed rate	85	266.103(c)(4)(iv)(C)(1)	266.103(c)(4)(iv)(C)(1)	X			
specifications the continuous monitor shall meet	85	266.103(c)(4)(iv)(C)(2)	266.103(c)(4)(iv)(C)(2)	X			
		266.103(c)(4)(iv)(C)(2)(i)	266.103(c)(4)(iv)(C)(2)(i)	X			
	85,94	266.103(c)(4)(iv)(C)(2)(ii)	266.103(c)(4)(iv)(C)(2)(ii)	X			
operating limit for feed rate of each metal established based on compliance test data as the specified average	85	266.103(c)(4)(iv)(C)(3)	266.103(c)(4)(iv)(C)(3)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
feed rate limits for metals, total chloride and chlorine, and ash established and monitored based on feedstream concentration and flow rate; flow rate continuously monitored as per 266.103(c)(4)(iv)(A)-(C)	85	266.103(c)(4)(iv)(D)	266.103(c)(4)(iv)(D)	X			
language of statement to accompany the certification of compliance	85	266.103(c)(4)(v)	266.103(c)(4)(v)	X			
if required to comply with 266.104(c) or 266.103(a)(5)(i)(D) HC controls, conditioned gas monitoring system may be used in conformance with 266, Appendix IX specifications, provided certification of compliance is submitted without 266.103(c)(7) time extension; owners and operators of facilities electing to comply with 266.104(f) alternative hydrocarbon provision and requesting a 266.103(c)(7)(ii)(B) time extension	85,111	266.103(c)(5)	266.103(c)(5)	X			
special operating requirements for industrial furnaces that recycle collected particulate matter from air pollution control system:	85	266.103(c)(6)	266.103(c)(6)	X			
266, Appendix IX operating requirements in "Alternative Method to Implement the Metals Controls" if complying with 266.103(c)(3)(ii)(A)	85	266.103(c)(6)(i)	266.103(c)(6)(i)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
operating requirements of 266.103(c)(3)(ii)(B) if complying with that paragraph	85	266.103(c)(6)(ii)	266.103(c)(6)(ii)	X			
requirements if fail to submit complete certification of compliance for 266.104-266.107 emissions standards by August 21, 1992:	85	266.103(c)(7)(i)	266.103(c)(7)(i)	X			
stop burning hazardous waste and begin 266.103(i) closure	85,94	266.103(c)(7)(i)(A)	266.103(c)(7)(i)(A)	X			
limit hazardous waste burning only for purposes of compliance testing (and pretesting to prepare for compliance testing) to a total period of 720 hours beginning August 21, 1992; submit notification to Director by August 21, 1992, stating operation under restricted interim status and intention to resume hazardous waste burning; submit complete certification of compliance by August 23, 1993	85,94	266.103(c)(7)(i)(B)	266.103(c)(7)(i)(B)	X			
obtain case-by-case time extension under 266.103(c)(7)(ii)	85	266.103(c)(7)(i)(C)	266.103(c)(7)(i)(C)	X			
condition under which a case-by-case time extension may be requested for any 266.103(c) time limit	85	266.103(c)(7)(ii)	266.103(c)(7)(ii)	X			
in granting extension, Director may apply specified conditions	85	266.103(c)(7)(ii)(A)	266.103(c)(7)(ii)(A)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
if time extension requested to enable facility to comply with alternative hydrocarbon provisions of 266.104(f) and to obtain RCRA permit because 266.104(c) HC limit cannot be met:	85,111	266.103(c)(7)(ii)(B)	266.103(c)(7)(ii)(B)	X			
what Director shall consider:	85	266.103(c)(7)(ii)(B)(1)	266.103(c)(7)(ii)(B)(1)	X			
determine if complete Part B permit application that includes 270.22(b) information has been submitted	85	266.103(c)(7)(ii)(B)(1)(i)	266.103(c)(7)(ii)(B)(1)(i)	X			
consider if good faith effort to certify compliance with all other emission controls has been made	85,94	266.103(c)(7)(ii)(B)(1)(ii)	266.103(c)(7)(ii)(B)(1)(ii)	X			
12 if extension granted, require facility to operate under 266.104(f)(1) baseline CO and HC flue gas concentration limits	85,94	266.103(c)(7)(ii)(B)(2)	266.103(c)(7)(ii)(B)(2)	X			
submit at any time a revised certification of compliance under specific procedures:	85	266.103(c)(8)	266.103(c)(8)	X			
prior to submittal, may not burn hazardous waste for more than 720 hours under operating conditions that exceed those in current certification of compliance; such burning conducted only to determine if 266.104-266.107 emissions standards can be met under revised conditions	85	266.103(c)(8)(i)	266.103(c)(8)(i)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
at least 30 days prior to first burning under revised conditions, notify Director and submit specific information:	85	266.103(c)(8)(ii)	266.103(c)(8)(ii)	X			
EPA facility ID number, facility name, contact person, telephone number and address	85	266.103(c)(8)(ii)(A)	266.103(c)(8)(ii)(A)	X			
operating conditions owner/operator is seeking to revise and description of changes that prompted need to revise	85	266.103(c)(8)(ii)(B)	266.103(c)(8)(ii)(B)	X			
determination that under revised operating conditions, 266.104-266.107 standards unlikely to be exceeded; 266.103(b)(2) information for documentation	85	266.103(c)(8)(ii)(C)	266.103(c)(8)(ii)(C)	X			
complete emissions testing protocol for pretesting and new compliance test, including schedule for 266.104-266.107 emission standards compliance; 30-day prior written notice if revision in compliance test date	85	266.103(c)(8)(ii)(D)	266.103(c)(8)(ii)(D)	X			
conduct compliance test under revised operating conditions and submitted protocol to determine 266.104-266.107 emissions standards compliance	85	266.103(c)(8)(iii)	266.103(c)(8)(iii)	X			
submit revised certification of compliance under 266.103(c)(4)	85	266.103(c)(8)(iv)	266.103(c)(8)(iv)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
recertification of compliance within three years; if recertification under new operating conditions, 266.103(c)(8) compliance	85	266.103(d)	266.103(d)	X			
if noncompliance with interim status compliance schedule, burning is to terminate on date deadline is missed, closure to begin under 266.103(l), and no resumption of burning except under 270.66 operating permit; criteria for compliance with 266.103(l), 266.112(d)(2) and 266.113 provisions	85,96	266.103(e)	266.103(e)	X			
no hazardous waste as feed during start-up and shut-down unless device is operating within certification conditions	85	266.103(f)	266.103(f)	X			
during 266.103(c)(3) compliance test and upon certification of compliance, automatic waste feed cutoff required; additional requirements include:	85	266.103(g)	266.103(g)	X			
maintenance of minimum combustion chamber temperature while hazardous waste or residues remain in chamber to minimize emissions of organic compounds	85,94	266.103(g)(1)	266.103(g)(1)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
if compliance with combustion chamber temperature limit is based on hourly rolling average, minimum temperature during compliance test is averaged over all runs of the lowest hourly rolling average for each run	85	266.103(g)(1)(i)	266.103(g)(1)(i)	X			
if compliance with combustion chamber temperature limit is based on instantaneous temperature measurement, minimum temperature during compliance test is time-weighted average during all test runs	85	266.103(g)(1)(ii)	266.103(g)(1)(ii)	X			
continued monitoring of operating parameters with limits during cutoff; no restart of hazardous waste feed until parameters comply with limits established in compliance certification	85	266.103(g)(2)	266.103(g)(2)	X			
requirements for controlling fugitive emissions	85	266.103(h)	266.103(h)	X			
		266.103(h)(1)	266.103(h)(1)	X			
		266.103(h)(2)	266.103(h)(2)	X			
		266.103(h)(3)	266.103(h)(3)	X			
cease burning hazardous waste when changes in combustion properties, feed rates, feed stocks/fuels or design or operating conditions deviate from limits specified in compliance certification	85	266.103(i)	266.103(i)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
owner or operator, while burning hazardous waste, must monitor and record:	85	266.103(j)(1)	266.103(j)(1)	X			
specified feed rates and composition of specified materials to ensure conformance with certification	85	266.103(j)(1)(i)	266.103(j)(1)(i)	X			
CO, HC and oxygen on a continuous basis as specified; monitors installed, operated and maintained as per 266, Appendix IX methods	85	266.103(j)(1)(ii)	266.103(j)(1)(ii)	X			
sampling and analysis as requested by Director to verify compliance with 266.104-266.107 standards	85	266.103(j)(1)(iii)	266.103(j)(1)(iii)	X			
daily visual inspection of boiler or industrial furnace and associated equipment when they contain hazardous waste	85	266.103(j)(2)	266.103(j)(2)	X			
test automatic feed cutoff system and associated alarms at least once every 7 days when hazardous waste is burned unless specified conditions are demonstrated; operational testing at least once every 30 days	85	266.103(j)(3)	266.103(j)(3)	X			
monitoring and inspection data recorded and placed in operating log	85	266.103(j)(4)	266.103(j)(4)	X			
all 266.103-required information and data kept in facility operating record until closure of the boiler or industrial furnace unit	85,96	266.103(k)	266.103(k)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
remove all hazardous waste and hazardous waste residues at closure and comply with 265.111-265.115	85	266.103(l)	266.103(l)	X			
<b>STANDARDS TO CONTROL ORGANIC EMISSIONS</b>							
except as 266.104(a)(3) provides, DRE of 99.99% required for all organic hazardous constituents; demonstration during trial burn for each POHC in permit for each waste feed; DRE equation	85,94	266.104(a)(1)	266.104(a)(1)	X			
POHC compliance with DRE requirements to be demonstrated in trial burn in conformance with 270.66 procedures; designation of POHCs for each waste feed by Director based on degree of difficulty of destruction and on waste feed concentrations considering analyses submitted with Part B; 261, Appendix VIII compounds unless demonstration of other compound is suitable indicator of DRE requirements	85	266.104(a)(2)	266.104(a)(2)	X			
DRE of 99.9999% for F020-F023, F026 or F027 as determined from 266.104(a)(1) equation; notification of intent to burn such wastes	85,94	266.104(a)(3)	266.104(a)(3)	X			
owners and operators of boilers operating under 266.110 requirements are exempt from DRE trial burn	85	266.104(a)(4)	266.104(a)(4)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
owners and operators of boilers or industrial furnaces in compliance with 266.109(a) are exempt from DRE trial burn	85	266.104(a)(5)	266.104(a)(5)	X			
except as 266.104(c) provides, CO stack gas concentration cannot exceed 100 ppmv on an hourly rolling average basis, continuously corrected to 7% oxygen, dry gas basis	85	266.104(b)(1)	266.104(b)(1)	X			
continuous monitoring of CO and oxygen in conformance with 266, Appendix IX specifications	85,94	266.104(b)(2)	266.104(b)(2)	X			
demonstration of 100 ppmv CO compliance during trial burn or compliance test; highest hourly rolling average CO must not exceed 100 ppmv	85	266.104(b)(3)	266.104(b)(3)	X			
stack gas concentration of CO may exceed 100 ppmv if HC concentrations do not exceed 20 ppmv; exception under 266.104(f)	85	266.104(c)(1)	266.104(c)(1)	X			
HC limits established on hourly rolling average basis, reported as propane, continuously corrected to 7% oxygen, dry gas basis	85	266.104(c)(2)	266.104(c)(2)	X			
HC continuously monitored under 266, Appendix IX specifications; CO and oxygen continuously monitored under 266.104(b)(2)	85,94	266.104(c)(3)	266.104(c)(3)	X			

**US EPA ARCHIVE DOCUMENT**

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
alternative CO standard based on trial burn data (new facility) and compliance test (interim status facility); definition and implementation	85	266.104(c)(4)	266.104(c)(4)	X			
industrial furnaces that feed hazardous waste for purpose other than solely as an ingredient at any location other than end where products are normally discharged and fuels are normally fired must comply with 266.104(c) or (f) hydrocarbon limits, irrespective of whether 266.104(b) standard is met	85	266.104(d)	266.104(d)	X			
site-specific risk assessment for specific boilers and industrial furnaces to demonstrate that chlorinated dibenzo- <i>p</i> -dioxins and dibenzofurans emissions do not result in increased lifetime cancer risk exceeding 1 in 100,000 MEI; assessment requirements:	85	266.104(e)	266.104(e)	X			
determine emission rates of certain tetraocta congeners during trial burn or compliance test using 266, Appendix IX Method 23	85,94	266.104(e)(1)	266.104(e)(1)	X			
estimate 2,3,7,8-TCDD toxicity equivalence of specified congeners using 266, Appendix IX procedures; formula for estimation of equivalent emission rate	85,94	266.104(e)(2)	266.104(e)(2)	X			

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
conduct dispersion modeling using recommended methods to predict maximum annual average off-site ground level concentrations of 2,3,7,8-TCDD equivalents; maximum annual average concentration used when a person resides on-site; wording should refer to Appendix W, Part 51 rather than Appendix X, Part 266, methods	85,125	266.104(e)(3)	266.104(e)(3)	X			
specified 2,3,7,8-TCDD ratio shall not exceed 1.0	85,94,96	266.104(e)(4)	266.104(e)(4)	X			
for industrial furnaces that cannot meet the 20 ppmv HC limit because of organic matter in raw material, Director may establish alternative HC limit on case-by-case basis; cement kilns equipped with by-pass duct meeting 266.104(g) requirements not eligible for alternative limit	85	266.104(f)	266.104(f)	X			
demonstrate that facility is designed and operated to minimize HC emissions from fuels and raw materials and that the facility is producing normal products under normal operating conditions feeding normal feedstocks and fuels when baseline HC (and CO) level is determined; baseline HC level and CO level defined; must be multiple baseline levels under certain conditions	85,111	266.104(f)(1)	266.104(f)(1)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
develop approach to monitor over time changes in facility operation that could reduce baseline HC level	85	266.104(f)(2)	266.104(f)(2)	X			
conduct emissions testing during trial burn to:	85	266.104(f)(3)	266.104(f)(3)	X			
determine baseline HC (and CO) level	85	266.104(f)(3)(i)	266.104(f)(3)(i)	X			
demonstrate that HC (and CO) levels do not exceed baseline level when hazardous waste is burned	85..	266.104(f)(3)(ii)	266.104(f)(3)(ii)	X			
identify types and concentrations of 261, Appendix VIII organic compounds that are emitted; conduct dispersion modeling; on-site ground level concentrations evaluated if person resides on-site	85,94	266.104(f)(3)(iii)	266.104(f)(3)(iii)	X			
		266.104(f)(3)(iii)(A)	266.104(f)(3)(iii)(A)	X			
	85	266.104(f)(3)(iii)(B)	266.104(f)(3)(iii)(B)	X			
demonstrate that maximum annual average ground level concentrations of 266.104(f)(3)(iii) compounds do not exceed specified levels		266.104(f)(3)(iv)	266.104(f)(3)(iv)	X			
		266.104(f)(3)(iv)(A)	266.104(f)(3)(iv)(A)	X			
		266.104(f)(3)(iv)(B)	266.104(f)(3)(iv)(B)	X			
	85	266.104(f)(3)(iv)(C)	266.104(f)(3)(iv)(C)	X			
monitor and report all 266.104(f) hydrocarbon levels as 266.104(c)(1)&(2) specify	85	266.104(f)(4)	266.104(f)(4)	X			
cement kilns may comply with CO and HC limits under 266.104(b)-(d) by monitoring in the by-pass duct provided:	85	266.104(g)	266.104(g)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
fire hazardous waste only into the kiln	85	266.104(g)(1)	266.104(g)(1)	X			
14 by-pass duct diverts minimum of 10% of kiln off-gas into duct	85,94	266.104(g)(2)	266.104(g)(2)	X			
simultaneous demonstration of 266.104 compliance by emissions testing or during separate runs under identical operating conditions; data to demonstrate compliance with CO and HC limits or to establish alternative limits must be obtained during DRE testing, CDD/CDF testing and comprehensive organic emissions testing	85	266.104(h)	266.104(h)	X			
compliance with permit operating requirements regarded as compliance with 266.104; if such compliance is insufficient, modification or revocation and reissuance of permit under 270.41	85	266.104(i)	266.104(i)	X			
<b>STANDARDS TO CONTROL PARTICULATE MATTER</b>							
particulate matter emissions limited to 180 milligrams per dry standard cubic meter after specified correction using Part 60, Appendix A, Methods 1-5 and 266, Appendix IX procedures	85	266.105(a)	266.105(a)	X			
owner or operator meeting 266.109(b) requirements for low risk waste exemption is exempt from particulate matter standard	85	266.105(b)	266.105(b)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
compliance with permit operating requirements regarded as compliance with 266.105; if such compliance is insufficient, modification or revocation and reissuance of permit under 270.41	85	266.105(c)	266.105(c)	X			
<b>STANDARDS TO CONTROL METALS EMISSIONS</b>							
compliance with 266.106(b), (c), (d), (e), or (f) for each 266.106(b) metal that is detectable in waste using specified procedures	85,94	266.106(a)	266.106(a)	X			
Tier I feed rate screening limits for metals specified in 266, Appendix I as a function of terrain-adjusted effective stack height and terrain and land use in facility vicinity; criteria for ineligible facilities in 266.107(b)(7)	85	266.106(b)	266.106(b)	X			
feed rates of antimony, barium, lead, mercury, thallium and silver in all feedstreams shall not exceed 266, Appendix I screening limits	85	266.106(b)(1)	266.106(b)(1)	X			
what feed rate screening limits for antimony, barium, mercury, thallium, and silver are based on	85	266.106(b)(1)(i)	266.106(b)(1)(i)	X			
		266.106(b)(1)(i)(A)	266.106(b)(1)(i)(A)	X			
		266.106(b)(1)(i)(B)	266.106(b)(1)(i)(B)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
what feed rate screening limit for lead is based on	85	266.106(b)(1)(ii)	266.106(b)(1)(ii)	X			
		266.106(b)(1)(ii)(A)	266.106(b)(1)(ii)(A)	X			
		266.106(b)(1)(ii)(B)	266.106(b)(1)(ii)(B)	X			
		266.106(b)(1)(ii)(C)	266.106(b)(1)(ii)(C)	X			
feed rates of arsenic, cadmium, beryllium and chromium in all feedstreams shall not exceed values derived from 266, Appendix I screening limits; feed rate limit equation	85,94	266.106(b)(2)(i)	266.106(b)(2)(i)	X			
what feed rate screening limits for carcinogenic metals are based on	85	266.106(b)(2)(ii)	266.106(b)(2)(ii)	X			
		266.106(b)(2)(ii)(A)	266.106(b)(2)(ii)(A)	X			
	85,94	266.106(b)(2)(ii)(B)	266.106(b)(2)(ii)(B)	X			
equation for terrain-adjusted effective stack height (TESH)	85	266.106(b)(3)(i)	266.106(b)(3)(i)	X			
stack height may not exceed 40 CFR 51.100(ii) good engineering practice	85	266.106(b)(3)(ii)	266.106(b)(3)(ii)	X			
if TESH for a particular facility is not listed in table in appendices, nearest lower TESH to be used; if TESH $\leq$ 4 meters, a value of 4 meters shall be used	85	266.106(b)(3)(iii)	266.106(b)(3)(iii)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
screening limits function of noncomplex or complex terrain; criteria; use U.S. Geological Survey 7.5-minute topographic maps	85	266.106(b)(4)	266.106(b)(4)	X			
screening limits function of urban or rural land use; determination using 266, Appendix IX or X	85,94	266.106(b)(5)	266.106(b)(5)	X			
facilities with multiple stacks must comply with screening limits for all units assuming all hazardous waste is fed into device with worst-case stack; worst-case stack equation, with lowest K value the worst-case stack	85,94	266.106(b)(6)	266.106(b)(6)	X			
criteria under which Tier III standards or Adjusted Tier I feed rate screening limits apply instead of Tier I and Tier II screening limits	85,111	266.106(b)(7)	266.106(b)(7)	X			
		266.106(b)(7)(i)	266.106(b)(7)(i)	X			
		266.106(b)(7)(ii)	266.106(b)(7)(ii)	X			
		266.106(b)(7)(iii)	266.106(b)(7)(iii)	X			
		266.106(b)(7)(iv)	266.106(b)(7)(iv)	X			
		266.106(b)(7)(v)	266.106(b)(7)(v)	X			
monitor feed rate of metals in each feedstream to ensure screening limits are not exceeded	85	266.106(b)(8)	266.106(b)(8)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
Tier II emission rate screening limits function of stack height and terrain and land use in facility vicinity; ineligible facilities comply with 266.106(b)(7) criteria.	85	266.106(c)	266.106(c)	X			
emission rates of antimony, barium, lead, mercury, thallium and silver shall not exceed 266, Appendix I screening limits	85	266.106(c)(1)	266.106(c)(1)	X			
emission rates of arsenic, cadmium, beryllium and chromium shall not exceed values derived from 266, Appendix I screening limits; emission rate equation	85,94	266.106(c)(2)	266.106(c)(2)	X			
emission rate limits implemented by limiting individual metal feed rates to trial burn or compliance test levels; averaging periods; monitoring of metals feed rate in each feedstream to ensure compliance with 266.102 or 266.103 limits	85	266.106(c)(3)	266.106(c)(3)	X			
266.106(b) definitions and limitations for specified terms also apply to 266.106(c) Tier II emission rate screening limits	85	266.106(c)(4)	266.106(c)(4)	X			
facilities with multiple stacks must comply with emissions screening limits for any such stacks assuming all hazardous waste is fed into device with worst-case stack	85	266.106(c)(5)(i)	266.106(c)(5)(i)	X			
worst-case stack determined by 266.106(b)(6) procedures	85	266.106(c)(5)(ii)	266.106(c)(5)(ii)	X			

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
for each metal, total emissions from those stacks shall not exceed worst-case stack screening limit	85	266.106(c)(5)(iii)	266.106(c)(5)(iii)	X			
facilities complying with either Tier III or Adjusted Tier I controls	111	266.106(d)	266.106(d)	X			
15 conformance with Tier III metals control demonstrated by emissions testing; conformance with either Tier III or Adjusted Tier I metals controls demonstrated by air dispersion modeling; demonstration that acceptable ambient levels are not exceeded	85,111	266.106(d)(1)	266.106(d)(1)	X			
266, Appendices IV and V list acceptable ambient levels; RACs listed for noncarcinogenic metals and $10^{-5}$ RSDs listed for carcinogenic metals; RSD defined	85	266.106(d)(2)	266.106(d)(2)	X			
sum of the ratios of predicted ambient concentrations to risk-specific dose for all carcinogenic metals emitted shall not exceed 1.0; equation	85,94,111	266.106(d)(3)	266.106(d)(3)	X			
for noncarcinogenic metals, predicted maximum annual average off-site ground level concentration shall not exceed the RAC	85	266.106(d)(4)	266.106(d)(4)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
owners/operators with multiple stacks must conduct emissions testing and dispersion modeling to demonstrate that aggregate emissions do not exceed acceptable ambient levels; exception for facilities complying with Adjusted Tier I controls	85,111	266.106(d)(5)	266.106(d)(5)	X			
under Tier III, feed rates limited to trial burn or compliance test levels; averaging periods same as under 266.106(b)(1)(i)-(ii) and (b)(2)(ii); monitor metals feed rate in each feedstream to ensure 266.102 or 266.103 compliance	85	266.106(d)(6)	266.106(d)(6)	X			
Adjusted Tier I feed rate screening limits to account for site-specific dispersion modeling; how to estimate adjusted feed rate; feed rate screening limits for carcinogenic metals implemented under 266.106(b)(2)	85,94	266.106(e)	266.106(e)	X			
alternative implementation approaches approved by Director on a case-by-case basis for Tier II or III metals emission limits	85	266.106(f)(1)	266.106(f)(1)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
determination of 266.106(d) emissions limits for each noncarcinogenic and carcinogenic metal	85	266.106(f)(2)	266.106(f)(2)	X			
		266.106(f)(2)(i)	266.106(f)(2)(i)	X			
	85,94	266.106(f)(2)(ii)	266.106(f)(2)(ii)	X			
	85	266.106(f)(2)(ii)(A)	266.106(f)(2)(ii)(A)	X			
	85,94	266.106(f)(2)(ii)(B)	266.106(f)(2)(ii)(B)	X			
use 266, Appendix IX Multiple Metals Train to conduct emissions testing	85	266.106(g)(1)	266.106(g)(1)	X			
chromium emissions assumed to be hexavalent chromium unless owner/operator determines otherwise	85	266.106(g)(2)	266.106(g)(2)	X			
dispersion modeling conducted according to specified methods to predict maximum annual average off-site ground level concentration; on-site concentrations when person resides on-site	85,125	266.106(h)	266.106(h)	X			
compliance with 266.102 permit operating requirements regarded as 266.106 compliance unless evidence indicates otherwise; modification or revocation and re-issuance of permit under 270.41	85	266.106(i)	266.106(i)	X			
<b>STANDARDS TO CONTROL HYDROGEN CHLORIDE (HCl) AND CHLORINE GAS (Cl<sub>2</sub>) EMISSIONS</b>							
compliance with HCl and Cl <sub>2</sub> controls under 266.107(b), (c) or (e)	85,94,111	266.107(a)	266.107(a)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
Tier I feed rate screening limits for total chlorine specified in 266, Appendix II as a function of stack height and terrain and land use in facility vicinity; feed rate of total chlorine and chloride in all feedstreams not to exceed specified levels	85	266.107(b)(1)	266.107(b)(1)	X			
Tier II emission rate screening limits for HCl and Cl <sub>2</sub> specified in 266, Appendix III as a function of terrain-adjusted effective stack height and terrain and land use in facility vicinity; stack emission rates not to exceed specified levels	85,94	266.107(b)(2)	266.107(b)(2)	X			
266.106(b) definitions and limitations for specified terms also apply to 266.107(b) screening limits	85,94	266.107(b)(3)	266.107(b)(3)	X			
facilities with multiple stacks subject to HCl or Cl <sub>2</sub> emissions controls must comply with Tier I and II screening limits assuming all hazardous waste is fed into device with worst-case stack	85	266.107(b)(4)	266.107(b)(4)	X			
worst-case stack determined by 266.106(b)(6) procedures	85	266.107(b)(4)(i)	266.107(b)(4)(i)	X			
under Tier I, total feed rate of chlorine and chloride to all subject devices not to exceed worst-case stack screening limit	85	266.107(b)(4)(ii)	266.107(b)(4)(ii)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
under Tier II, total HCl and Cl <sub>2</sub> emissions from all subject stacks not to exceed worst-case stack screening limit	85	266.107(b)(4)(iii)	266.107(b)(4)(iii)	X			
conformance with Tier III controls demonstrated by HCl and Cl <sub>2</sub> emissions testing, air dispersion modeling, and demonstration that acceptable ambient levels are not exceeded	85	266.107(c)(1)	266.107(c)(1)	X			
266, Appendix IV lists RACs for HCl and Cl <sub>2</sub>	85	266.107(c)(2)	266.107(c)(2)	X			
facilities with multiple stacks subject to HCl or Cl <sub>2</sub> emissions controls must conduct emissions testing and dispersion modeling to demonstrate that aggregate emissions do not exceed acceptable ambient levels for HCl and Cl <sub>2</sub>	85	266.107(c)(3)	266.107(c)(3)	X			
16 HCl and Cl <sub>2</sub> controls implemented by limiting feed rate of total chlorine and chloride in all feedstreams; feed rate under Tier I limited to Tier I screening limits; feed rate under Tiers II and III limited to trial burn or compliance test feed rates; feed rate limits based on:	85	266.107(d)	266.107(d)	X			
		266.107(d)(1)	266.107(d)(1)	X			
	85,94	266.107(d)(2)	266.107(d)(2)	X			
adjusted Tier I feed rate screening limits to account for site-specific dispersion modeling; how to determine these adjusted rates	85	266.107(e)	266.107(e)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
emissions testing for HCl and Cl <sub>2</sub> conducted using 266, Appendix IX procedures	85	266.107(f)	266.107(f)	X			
dispersion modeling conducted according to 266.106(h) provisions	85	266.107(g)	266.107(g)	X			
compliance with 266.102 permit operating requirements regarded as 266.107 compliance unless evidence indicates otherwise; modification or revocation and re-issuance of permit under 270.41	85	266.107(h)	266.107(h)	X			
<b>SMALL QUANTITY ON-SITE BURNER EXEMPTION</b>							
owners and operators that burn hazardous waste in on-site boiler or industrial furnace exempt from 266 Subpart H requirements provided:	85,94	266.108(a)	266.108(a)	X			
quantity of hazardous waste burned for a calendar month does not exceed limits shown in table titled "Exempt Quantities for Small Quantity Burner Exemption" based on 266.106(b)(3) terrain-adjusted effective stack height; table	85,94	266.108(a)(1)	266.108(a)(1)	X			
maximum hazardous waste firing rate does not exceed 1% of total fuel requirements on a total heat input or mass input basis, whichever results in the lower mass feed rate of hazardous waste	85,96	266.108(a)(2)	266.108(a)(2)	X			
minimum heating value of 5,000 Btu/lb	85	266.108(a)(3)	266.108(a)(3)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
does not contain F020-F023, F026 or F027	85	266.108(a)(4)	266.108(a)(4)	X			
if mixed with non-hazardous waste, compliance with 266.108(a) quantity before mixing	85	266.108(b)	266.108(b)	X			
equation for implementing 266.108(a)(1) quantity limits if burning in more than one exempt on-site boiler or industrial furnace	85,94,111	266.108(c)	266.108(c)	X			
one-time signed, written notification requirements for small quantity burner exemption	85	266.108(d)	266.108(d)	X			
		266.108(d)(1)	266.108(d)(1)	X			
		266.108(d)(2)	266.108(d)(2)	X			
		266.108(d)(3)	266.108(d)(3)	X			
maintain for at least 3 years sufficient records documenting quantity firing rate and heating value limits compliance, including quantity burned per calendar month and heating value	85	266.108(e)	266.108(e)	X			
<b>LOW RISK WASTE EXEMPTION</b>							
waiver of 266.104(a) DRE standard if device is operated in conformance with 266.109(a)(1) and burning will not result in unacceptable adverse health effects as per 266.109(a)(2) procedures	85	266.109(a)	266.109(a)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
operating requirements for device	85	266.109(a)(1)	266.109(a)(1)	X			
	85,94,96	266.109(a)(1)(i)	266.109(a)(1)(i)	X			
		266.109(a)(1)(ii)	266.109(a)(1)(ii)	X			
		266.109(a)(1)(iii)	266.109(a)(1)(iii)	X			
	85	266.109(a)(1)(iv)	266.109(a)(1)(iv)	X			
procedures to demonstrate that hazardous waste burning will not pose unacceptable adverse public health effects		266.109(a)(2)	266.109(a)(2)	X			
		266.109(a)(2)(i)	266.109(a)(2)(i)	X			
		266.109(a)(2)(ii)	266.109(a)(2)(ii)	X			
		266.109(a)(2)(iii)	266.109(a)(2)(iii)	X			
		266.109(a)(2)(iii)(A)	266.109(a)(2)(iii)(A)	X			
	85	266.109(a)(2)(iii)(B)	266.109(a)(2)(iii)(B)	X			
		266.109(a)(2)(iv)	266.109(a)(2)(iv)	X			
	85,94	266.109(a)(2)(iv)(A)	266.109(a)(2)(iv)(A)	X			
		266.109(a)(2)(iv)(B)	266.109(a)(2)(iv)(B)	X			
	85	266.109(a)(2)(iv)(C)	266.109(a)(2)(iv)(C)	X			
conditions under which the 266.105 particulate matter standard is waived		266.109(b)	266.109(b)	X			
	85	266.109(b)(1)	266.109(b)(1)	X			
	85,94	266.109(b)(2)	266.109(b)(2)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
<b>WAIVER OF DRE TRIAL BURN FOR BOILERS</b>							
boilers operating under 266.110 requirements and that do not burn F020-F023, F026 or F027 considered in compliance with 266.104(a) DRE standard, and trial burn to demonstrate DRE is waived; when burning hazardous waste:	85	266.110	266.110	X			
"primary fuel" defined; minimum of 50% primary fuel firing rate, determined on total heat or mass input basis, whichever results in the greater mass feed rate	85,96	266.110(a)	266.110(a)	X			
boiler load defined and not less than 40%	85	266.110(b)	266.110(b)	X			
minimum as-fired heating value of 8,000 Btu/lb	85	266.110(c)	266.110(c)	X			
conformance with 266.104(b) (1) carbon monoxide standard; boilers subject to 266.110 DRE waiver not eligible for 266.104(c) alternative carbon monoxide standard	85	266.110(d)	266.110(d)	X			
boiler must be water-tube type that does not feed fuel using a stoker or stoker type mechanism	85	266.110(e)	266.110(e)	X			
conditions under which hazardous waste shall be fired directly into primary fuel flame zone of combustion chamber with an air or steam, mechanical or rotary cup atomization system	85	266.110(f)	266.110(f)	X			
		266.110(f)(1)	266.110(f)(1)	X			
		266.110(f)(2)	266.110(f)(2)	X			
		85,94	266.110(f)(3)	266.110(f)(3)	X		
	85	266.110(f)(4)	266.110(f)(4)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIV-ALENT	LESS STRIN-GENT	MORE STRIN-GENT	BROADE R IN SCOPE
<b>STANDARDS FOR DIRECT TRANSFER</b>							
266.111 regulations apply to boilers and industrial furnaces subject to 266.102 or 266.103 if direct transfer of hazardous waste from transport vehicle to boiler or industrial furnace without use of storage unit	85	266.111(a)	266.111(a)	X			
for 266.111, terms have meanings given in 266.111(b)(1)	85	266.111(b)(1) intro	266.111(b)(1) intro	X			
"direct transfer equipment"	85	266.111(b)(1)	266.111(b)(1)	X			
"container"	85	266.111(b)(1)	266.111(b)(1)	X			
"tank systems" means direct transfer equipment when Subparts I and J of Parts 264 and 265 are referenced	85	266.111(b)(2)	266.111(b)(2)	X			
no direct transfer of pumpable hazardous waste from open-top container to boiler or industrial furnace	85	266.111(c)(1)	266.111(c)(1)	X			
direct transfer equipment requirements	85	266.111(c)(2)	266.111(c)(2)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
direct transfer of hazardous waste to boiler or industrial furnace conducted so that it does not result in any 266.111(c)(3)(i)-(vi) situation	85	266.111(c)(3)	266.111(c)(3)	X			
		266.111(c)(3)(i)	266.111(c)(3)(i)	X			
		266.111(c)(3)(ii)	266.111(c)(3)(ii)	X			
		266.111(c)(3)(iii)	266.111(c)(3)(iii)	X			
		266.111(c)(3)(iv)	266.111(c)(3)(iv)	X			
		266.111(c)(3)(v)	266.111(c)(3)(v)	X			
		266.111(c)(3)(vi)	266.111(c)(3)(vi)	X			
conditions under which hazardous waste shall not be placed in direct transfer equipment	85	266.111(c)(4)	266.111(c)(4)	X			
appropriate controls and practices to prevent spills and overflows from direct transfer equipment or its secondary containment system	85	266.111(c)(5)	266.111(c)(5)	X			
		266.111(c)(5)(i)	266.111(c)(5)(i)	X			
		266.111(c)(5)(ii)	266.111(c)(5)(ii)	X			
applying 266.111(b)(1) definition of container, owners and operators must comply with:	85	266.111(d)	266.111(d)	X			
264.175 containment requirements	85	266.111(d)(1)	266.111(d)(1)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
use and management requirements of Subpart I, Part 265 requirements, except 265.170 and 265.174; compliance with specified maintenance and protective distances in lieu of 265.176 requirements; written certification by local fire marshall to be kept on file	85,96	266.111(d)(2)	266.111(d)(2)	X			
264.178 closure requirements	85	266.111(d)(3)	266.111(d)(3)	X			
direct transfer equipment must meet following requirements:	85	266.111(e)	266.111(e)	X			
secondary containment requirements for new and existing equipment	85	266.111(e)(1)	266.111(e)(1)	X			
		266.111(e)(1)(i)	266.111(e)(1)(i)	X			
		266.111(e)(1)(ii)	266.111(e)(1)(ii)	X			
for existing direct transfer equipment without secondary containment, determination whether leaking or unfit for use; written assessment reviewed and certified by qualified, registered professional engineer in accordance with 270.11(d) by August 21, 1992	85	266.111(e)(2)(i)	266.111(e)(2)(i)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
minimum considerations for assessment	85	266.111(e)(2)(ii)	266.111(e)(2)(ii)	X			
		266.111(e)(2)(ii)(A)	266.111(e)(2)(ii)(A)	X			
		266.111(e)(2)(ii)(B)	266.111(e)(2)(ii)(B)	X			
		266.111(e)(2)(ii)(C)	266.111(e)(2)(ii)(C)	X			
		266.111(e)(2)(ii)(D)	266.111(e)(2)(ii)(D)	X			
		266.111(e)(2)(ii)(E)	266.111(e)(2)(ii)(E)	X			
if, due to 266.111(e)(2)(i)&(ii) assessment, direct transfer equipment found to be leaking or unfit for use, compliance with 265.196(a) and (b)	85	266.111(e)(2)(iii)	266.111(e)(2)(iii)	X			
inspection requirements at least once each operating hour when transferring hazardous waste from container to boiler or industrial furnace	85	266.111(e)(3)(i)	266.111(e)(3)(i)	X			
		266.111(e)(3)(i)(A)	266.111(e)(3)(i)(A)	X			
		266.111(e)(3)(i)(B)	266.111(e)(3)(i)(B)	X			
		266.111(e)(3)(i)(C)	266.111(e)(3)(i)(C)	X			
inspect cathodic protection systems to ensure 265.195(b) compliance	85	266.111(e)(3)(ii)	266.111(e)(3)(ii)	X			
records of inspections maintained in operating record for at least 3 years	85	266.111(e)(3)(iii)	266.111(e)(3)(iii)	X			
265.192 compliance for design and installation of new ancillary equipment	85	266.111(e)(4)	266.111(e)(4)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
265.196 compliance for response to leaks or spills	85	266.111(e)(5)	266.111(e)(5)	X			
265.197 closure compliance, except 265.197(c)(2)-(4)	85	266.111(e)(6)	266.111(e)(6)	X			

17

**REGULATION OF RESIDUES**

residue derived from burning or processing of hazardous waste is not excluded under 261.4(b)(4), (7) or (8) unless device and owner or operator meet the following requirements:	85,94	266.112	266.112	X			
criteria the device must meet:	85	266.112(a)	266.112(a)	X			
	85,96	266.112(a)(1)	266.112(a)(1)	X			
		266.112(a)(2)	266.112(a)(2)	X			
	85	266.112(a)(3)	266.112(a)(3)	X			
demonstration by owner or operator that hazardous waste does not significantly affect residue by demonstrating conformance with either of two criteria:	85	266.112(b)	266.112(b)	X			
comparison of waste-derived residue with normal residue for 261, Appendix VIII constituents; procedures to be used	85	266.112(b)(1)	266.112(b)(1)	X			

18

US EPA ARCHIVE DOCUMENT

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
determination of concentrations of toxic constituents of concern in normal residue based on analyses of a minimum of 10 samples representing a minimum of 10 days of operation; determine compositing period not to exceed 24 hours; upper tolerance limit (at 95% confidence with a 95% proportion of the sample distribution) for the statistically-derived concentration; when to revise; how to determine the upper tolerance limit	85,96	266.112(b)(1)(i)	266.112(b)(1)(i)	X			
18 sampling and analysis of waste-derived residue to determine whether residue generated during each 24-hour period has concentrations of toxic constituents higher than 266.112(b)(1)(i) normal residue concentrations; if so, residue not excluded from definition of hazardous waste; toxic constituent concentrations based on analysis of samples obtained over 24-hour period; for multiple samples, concentration of toxic constituent is arithmetic mean; no results may be disregarded	85,96	266.112(b)(1)(ii)	266.112(b)(1)(ii)	X			

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
19 concentration of each nonmetal toxic constituent of concern in waste-derived residue must not exceed health-based limits specified in 266, Appendix VII or level detection using SW-846 analytical procedures; if no limit in Appendix VII, limit is 0.002 mg/kg or level of detection, whichever is higher; levels specified in appendix VII and default level of 0.002 micrograms/kg or level of detection as identified in Note 1 are administratively stayed; owner or operator must comply with alternative levels defined as land disposal restriction limits specified in § 268.43 for F039 nonwastewaters; compliance based on good-faith effort to detect constituents; demonstration of good-faith efforts; stay in effect until further administrative action is taken	85,111, †127	266.112(b)(2)(i)	266.112(b)(2)(i)	X			Note that Delaware is not applying for CL 127.
for metal constituents, in extract concentration obtained using 261.24 TCLP not to exceed 266, Appendix VII limits	85	266.112(b)(2)(ii)	266.112(b)(2)(ii)	X			

US EPA ARCHIVE DOCUMENT

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
sampling and analysis of waste-derived residue to determine whether residue generated during each 24-hour period has concentrations of toxic constituents higher than health-based levels; determination of toxic concentrations based on analysis of one or more samples obtained over 24-hour period; for multiple samples, concentration of toxic constituent is arithmetic mean of concentrations in samples; no results may be disregarded	96	266.112(b)(2)(iii)	266.112(b)(2)(iii)	X			
records to document 266.112 compliance to be retained until closure of boiler or industrial furnace unit; information to be recorded	85,96	266.112(c)	266.112(c)	X			
		266.112(c)(1)	266.112(c)(1)	X			
		266.112(c)(2)	266.112(c)(2)	X			
		266.112(c)(2)(i)	266.112(c)(2)(i)	X			
	85	266.112(c)(2)(ii)	266.112(c)(2)(ii)	X			

**APPENDIX I TO PART 266**

**TIER I AND TIER II FEED RATE AND EMISSIONS SCREENING LIMITS FOR METALS**

Tier I and Tier II Feed Rate and Emissions Screening Limits for Noncarcinogenic Metals for Facilities in Noncomplex Terrain (see 56 FR 7228 and 56 FR 32690 or the July 1, 1992 CFR)	85,94	Appendix I/ Table I-A	Appendix I/ Table I-A	X			
--	-------	--------------------------	--------------------------	---	--	--	--

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
Tier I and Tier II Feed Rate and Emissions Screening Limits for Noncarcinogenic Metals for Facilities in Noncomplex Terrain (see 56 FR 7229)	85	Appendix I/ Table I-B	Appendix I/ Table I-B	X			
Tier I and Tier II Feed Rate and Emissions Screening Limits for Noncarcinogenic Metals for Facilities in Complex Terrain (see 56 FR 7229)	85	Appendix I/ Table I-C	Appendix I/ Table I-C	X			
Tier I and Tier II Feed Rate and Emissions Screening Limits for Carcinogenic Metals for Facilities in Noncomplex Terrain (see 56 FR 7230 and 56 FR 32690, or the July 1, 1992 CFR)	85,94	Appendix I/ Table I-D	Appendix I/ Table I-D	X			
Tier I and Tier II Feed Rate and Emissions Screening Limits for Carcinogenic Metals for Facilities in Complex Terrain (see 56 FR 7230 and 56 FR 32690, or the July 1, 1992 CFR)	85,94	Appendix I/ Table I-E	Appendix I/ Table I-E	X			

APPENDIX II TO PART 266

TIER I FEED RATE LIMITS FOR TOTAL CHLORINE

20 Tier I feed rate screening limits for chlorine for facilities in noncomplex and complex terrain (see 56 FR 32690-32691 or the July 1, 1992 CFR)	85,94	Appendix II	Appendix II	X			
--	-------	-------------	-------------	---	--	--	--

US EPA ARCHIVE DOCUMENT

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE

**APPENDIX III TO PART 266**

**TIER II EMISSION RATE SCREENING LIMITS FOR FREE CHLORINE AND HYDROGEN CHLORIDE**

20 Tier II emissions screening limits for Cl <sub>2</sub> and HCl in non-complex and complex terrain (see 56 FR 32691 or the July 1, 1992 CFR)	85,94	Appendix III	Appendix III	X			
--	-------	--------------	--------------	---	--	--	--

**APPENDIX IV TO PART 266**

**REFERENCE AIR CONCENTRATIONS**

Constituents, CAS Nos. and RAC (see 56 FR 7232 and 56 FR 32691 or the July 1, 1992 CFR)	85,94	Appendix IV	Appendix IV	X			
---	-------	-------------	-------------	---	--	--	--

**APPENDIX V TO PART 266**

**RISK SPECIFIC DOSES**

Constituents, CAS Nos., Unit risk and RsD (see 56 FR 7232-7233 or the July 1, 1992 CFR)	85	Appendix V	Appendix V	X			
---	----	------------	------------	---	--	--	--

**APPENDIX VI TO PART 266**

**STACK PLUME RISE**

flow rates and exhaust temperatures (see 56 FR 7233-7234 or the July 1, 1992 CFR)	85	Appendix VI	Appendix VI	X			
---	----	-------------	-------------	---	--	--	--

**APPENDIX VII TO PART 266**

**HEALTH-BASED LIMITS FOR EXCLUSION OF WASTE-DERIVED RESIDUES**

Metals--TCLP Extract Concentration Limits (56 FR 7234 and 56 FR 32691 or the July 1, 1992 CFR)	85,94	Appendix VII	Appendix VII	X			
--	-------	--------------	--------------	---	--	--	--

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
Nonmetals--Residue Concentration Limits (see 56 FR 7234 and 56 FR 32691 or the July 1, 1992 CFR); include note regarding administrative stay of specified and default levels for constituents specified in § 266.112(b)(1) provided owner or operator complies with alternative levels defined in 266.112(b)(2)(i)	85,94, †127	Appendix VII	Appendix VII	X			Note that Delaware is not applying for CL 127.

**APPENDIX VIII TO PART 266**

**POTENTIAL PICs FOR DETERMINATION OF EXCLUSION OF WASTE-DERIVED RESIDUES**

PICs Found in Stack Effluents (see 56 FR 7235 and 56 FR 32691 or the July 1, 1992 CFR)	85,94	Appendix VIII	Appendix VIII	X			
--	-------	---------------	---------------	---	--	--	--

**APPENDIX IX TO PART 266**

**METHODS MANUAL FOR COMPLIANCE WITH BIF REGULATIONS**

21 Burning Hazardous Waste in Boilers and Industrial Furnaces (see 56 FR 32692-32795 or the July 1, 1992 CFR)	85,94	Appendix IX	Appendix IX	X			
21 Classification of Land Use Types (see 56 FR 32770 and 57 FR 38566)	85,94,111	Appendix IX/ Section 5.0/ Table 5.0-3	Appendix IX/ Section 5.0/ Table 5.0-3	X			
21, 22 ISCST Predicted Maximum Concentrations (see 56 FR 32771; 57 FR 38566; and 57 FR 44999)	85,94, 111,114	Appendix IX/ Section 5.0/ Table 5.0-4	Appendix IX/ Section 5.0/ Table 5.0-4	X			
21, 22 ISCST Predicted Maximum Concentrations (see 56 FR 32772-32773; 57 FR 38566; and 57 FR 44999)	85,94, 111,114	Appendix IX/ Section 5.0/ Table 5.0-5	Appendix IX/ Section 5.0/ Table 5.0-5	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
21 Simplified Land Use Classification Procedure for Compliance with Tier I and Tier II Limits (see 56 FR 32782-32783 or the July 1, 1991 CFR; and 57 FR 38566)	85,94,111	Appendix IX/ Section 6.0	Appendix IX/ Section 6.0	X			
21, 23 Statistical Methodology for Beville Residue Determinations (see 56 FR 42516 & 42517)	85,94,96	Appendix IX/ Section 7.0	Appendix IX/ Section 7.0	X			
21 Special procedures for chlorine, HCl and CL <sub>2</sub> (see 56 FR 32786-32787 and 56 FR 42512, Corrections 6 and 7 under Part 270; note these corrections should have been placed under Part 266)	85,94,96	Appendix IX/ Section 9.2	Appendix IX/ Section 9.2	X			
24 Statistics (see 56 FR 32796 or the July 1, 1992 CFR)	85,94	Appendix A to Appendix IX	Appendix A to Appendix IX	X			
25	APPENDIX X TO PART 266--(REMOVED)						
GUIDELINE ON AIR QUALITY MODELS (REVISED)							
Guidelines on air quality models	85,94	Appendix X	Appendix X	X			
APPENDIX XI TO PART 266							
LEAD-BEARING MATERIALS THAT MAY BE PROCESSED IN EXEMPT LEAD SMELTERS							
add new appendix addressing lead-bearing materials that may be processed in exempt lead smelters (see 56 FR 42517)	96	Appendix XI	Appendix XI	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE

**APPENDIX XII TO PART 266**

**NICKEL- OR CHROMIUM-BEARING MATERIALS THAT MAY BE PROCESSED IN EXEMPT NICKEL-CHROMIUM RECOVERY FURNACES**

add new appendix addressing nickel or chromium-bearing materials that may be processed in exempt nickel-chromium recovery furnaces (see 56 FR 42517)	96	Appendix XII	Appendix XII	X			
--	----	--------------	--------------	---	--	--	--

**PART 270 - EPA ADMINISTERED PERMIT PROGRAMS:  
THE HAZARDOUS WASTE PERMIT PROGRAM**

**SUBPART B - PERMIT APPLICATION**

**26 SPECIFIC PART B INFORMATION REQUIREMENTS FOR BOILERS AND INDUSTRIAL FURNACES BURNING HAZARDOUS WASTE**

owners and operators subject to 266.104-266.107 must conduct a trial burn and must submit a trial burn plan or results in accordance with 270.66	85	270.22(a)(1)	122.22(a)(1)	X			
waiver of trial burn to demonstrate conformance with a particular emission standard under 266.104-266.107 and 270.22(a)(2)-(a)(5)	85	270.22(a)(1)(i)	122.22(a)(1)(i)	X			
data in lieu of a trial burn as 270.22(a)(6) specifies	85	270.22(a)(1)(ii)	122.22(a)(1)(ii)	X			
boiler owners and operators seeking to be permitted under 266.104(a)(4) and 266.110, must submit documentation showing boiler compliance with special operating requirements at 266.110; trial burn waived	85	270.22(a)(2)(i)	122.22(a)(2)(i)	X			

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADEN SCOPE
information that must be submitted for boilers and industrial furnaces seeking to be permitted under the low risk waste provisions of 266.104(a)(5) and 266.109(a) without a trial burn	85	270.22(a)(2)(ii)	122.22(a)(2)(ii)	X			
		270.22(a)(2)(ii) (A)	122.22(a)(2)(ii) (A)	X			
	85,94	270.22(a)(2)(ii) (B)	270.22(a)(2)(ii) (B)	X			
		270.22(a)(2)(ii) (C)	122.22(a)(2)(ii) (C)	X			
	85	270.22(a)(2)(ii) (D)	122.22(a)(2)(ii) (D)	X			
		270.22(a)(2)(ii) (E)	122.22(a)(2)(ii) (E)	X			
information that must be submitted when seeking to be permitted under Tier I metals feed rate screening limits at 266.106(b)&(e) without a trial burn	85	270.22(a)(3)	122.22(a)(3)	X			
		270.22(a)(3)(i)	122.22(a)(3)(i)	X			
		270.22(a)(3)(ii)	122.22(a)(3)(ii)	X			
		270.22(a)(3)(iii)	122.22(a)(3)(iii)	X			
		270.22(a)(3)(iv)	122.22(a)(3)(iv)	X			
		270.22(a)(3)(v)	122.22(a)(3)(v)	X			
		270.22(a)(3)(vi)	122.22(a)(3)(vi)	X			
		270.22(a)(3)(vii)	122.22(a)(3)(vii)	X			
when seeking to be permitted under the low risk waste provisions of 266.109(b) which waives the particulate standard, submit documentation supporting 270.22(a)(2)(ii) and (a)(3) conformance	85	270.22(a)(4)	122.22(a)(4)	X			

US EPA ARCHIVE DOCUMENT

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
information to be submitted when seeking to be permitted under Tier I feed rate screening limits for total chloride and chlorine under 266.107(b)(1) and (e) provisions without a trial burn	85	270.22(a)(5)	122.22(a)(5)	X			
		270.22(a)(5)(i)	122.22(a)(5)(i)	X			
		270.22(a)(5)(ii)	122.22(a)(5)(ii)	X			
		270.22(a)(5)(iii)	122.22(a)(5)(iii)	X			
		270.22(a)(5)(iv)	122.22(a)(5)(iv)	X			
		270.22(a)(5)(v)	122.22(a)(5)(v)	X			
		270.22(a)(5)(vi)	122.22(a)(5)(vi)	X			
	85,94	270.22(a)(5)(vii)	122.22(a)(5)(vii)	X			
owner or operator may seek exemption from trial burn requirements demonstrating 266.104-266.107 conformance, by providing information from previous compliance testing of the device or compliance testing or trial burns of similar boilers or industrial furnaces; burning similar wastes under similar conditions 270.66 design and operation information required; conditions under which Director shall approve a permit application in lieu of a trial burn; additional information to be submitted	85,94	270.22(a)(6)	122.22(a)(6)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
for a waiver from any trial burn:	85	270.22(a)(6)(i)	122.22(a)(6)(i)	X			
		270.22(a)(6)(i)(A)	122.22(a)(6)(i)(A)	X			
		270.22(a)(6)(i)(B)	122.22(a)(6)(i)(B)	X			
		270.22(a)(6)(i)(C)	122.22(a)(6)(i)(C)	X			
for a waiver of DRE trial burn, basis for selection of the POHCs used in other burns which demonstrate 266.104(a) compliance; analysis should specify 261, Appendix VIII constituents in hazardous waste for which a permit is sought and any differences from POHCs for which data are provided	85	270.22(a)(6)(ii)	122.22(a)(6)(ii)	X			
minimum information to be submitted for industrial furnaces with organic matter in raw materials requesting an alternative HC limit under 266.104(f)	85	270.22(b)	122.22(b)	X			
	85,94	270.22(b)(1)	122.22(b)(1)	X			
	85	270.22(b)(2)	122.22(b)(2)	X			
		270.22(b)(3)	122.22(b)(3)	X			
		270.22(b)(4)	122.22(b)(4)	X			
		270.22(b)(4)(i)	122.22(b)(4)(i)	X			
		270.22(b)(4)(ii)	122.22(b)(4)(ii)	X			
		270.22(b)(5)	122.22(b)(5)	X			
270.22(b)(6)	122.22(b)(6)	X					

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
when seeking to be permitted under 266.106(f) alternative metals implementation approach, submit documentation that ensures 266.106(c) or (d) compliance and how approach can be implemented and monitored; provide other information as Director finds necessary	85	270.22(c)	122.22(c)	X			
describe automatic waste feed cutoff system, including any pre-alarm systems	85	270.22(d)	122.22(d)	X			
use of direct transfer operations requires submittal of information supporting 266.111 conformance	85	270.22(e)	122.22(e)	X			
demonstration of 266.112 conformance if claim is made that residues are excluded from regulation	85	270.22(f)	122.22(f)	X			

**SUBPART D - CHANGES TO PERMITS**

27

**PERMIT MODIFICATION AT THE REQUEST OF THE PERMITTEE**

replace "270.21" with "270.22" and "and 270.63" with "270.63 and 270.66"	94	270.42(c)(1)(iv)	270.42(c)(1)(iv)	X			
paragraph heading is changed to "Newly regulated wastes and units"	85	270.42(g)	122.42(g)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
add wording at end of paragraph regarding the continued management of hazardous waste in units newly regulated as hazardous waste management units; change "wates" to "wastes"	85,94	270.42(g)(1)	122.42(g)(1)	X			
insert "The unit" before "was in existence"; add "or newly regulated waste management unit" after "characterized waste"; add "or regulating the unit" at end of paragraph; change "effetive" to "effective"	85,94	270.42(g)(1)(i)	122.42(g)(1)(i)	X			
insert "The permittee" before "submits"; insert "or unit" after "waste"	85	270.42(g)(1)(ii)	122.42(g)(1)(ii)	X			
insert "The permittee" before "is"; insert "applicable" before "standards"; change "Part 265" to "Parts 265 and 266 of this chapter"	85	270.42(g)(1)(iii)	270.42(g)(1)(iii)	X			
delete "In the case of Classes 2 and 3 modifications, "; insert "The permittee" before "also"; replace "permit modification" with "Class 2 or 3 modification"; change "180 days after" to "180 days of"; add "or subjecting the unit to RCRA Subtitle C management standards" to end of paragraph	85,94	270.42(g)(1)(iv)	270.42(g)(1)(iv)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
28 insert "the permittee" before "certifies"; insert "each" before "such unit"; change "Part 265" to "requirements of Part 265 of this chapter for"; add ", or regulating the unit as a hazardous waste management unit" after "hazardous"; change "clarify" to "certify"; insert "all" before "these requirements"; change "shall lose" to "will lose"	85	270.42(g)(1)(v)	270.42(g)(1)(v)	X			
		270.42(g)(1)(iv)	270.42(g)(1)(iv)	X			

**SUBPART F - SPECIAL FORMS OF PERMITS**

**PERMITS FOR BOILERS AND INDUSTRIAL FURNACES BURNING HAZARDOUS WASTE**

new boilers and industrial furnaces subject to 270.66(b)-(f); those under interim status standards of 266.103 subject to 270.66(g)	85	270.66(a)	122.66(a)	X			
permit for new boiler or industrial furnace shall specify appropriate conditions for the following operating periods:	85	270.66(b)	122.66(b)	X			
pretrial burn period described; Director must establish in Pretrial Burn Period of permit conditions, allowable hazardous waste feed rates and operating conditions; extension of period for up to 720 additional hours; permit may be modified to reflect extension as per 270.42	85	270.66(b)(1)	122.66(b)(1)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
submittal of statement with Part B that suggests operating conditions for 266.104-266.107 compliance during period, including restrictions on 266.102(e) operating requirements	85	270.66(b)(1)(i)	122.66(b)(1)(i)	X			
review of Part B materials and specification by Director of requirements sufficient to meet 266.104-266.107 performance standards based on engineering judgment	85 111,114	270.66(b)(1)(ii)	270.66(b)(1)(ii)	X			
for duration of trial burn, Director establishes conditions in permit to determine feasibility of compliance with 266.104-266.107 standards and to determine adequate 266.102(e) operating conditions; applicants must propose a trial burn plan as per 270.66(c) and submit with Part B	85	270.66(b)(2)	122.66(b)(2)	X			
for defined minimum period immediately following trial burn, during which submission and review of trial burn results and modification of permit by Director occurs, Director establishes operating requirements most likely to ensure compliance with 266.104-266.107 standards	85	270.66(b)(3)(i)	122.66(b)(3)(i)	X			

**US EPA ARCHIVE DOCUMENT**

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
submission of statement with Part B that identifies operating conditions for 266.104-266.107 compliance during period, including restrictions on 266.102(e) operating requirements	85	270.66(b)(3)(ii)	122.66(b)(3)(ii)	X			
review and specification by Director of requirements sufficient to meet 266.104-266.107 performance standards based on engineering judgment	85	270.66(b)(3)(iii)	270.66(b)(3)(iii)	X			
for final period of operation, Director develops operating requirements in conformance with 266.102(e) and 266.104-266.107 standards; Director shall make necessary modifications to permit as per 270.42 based on trial burn results to ensure compliance	85,94	270.66(b)(4)	122.66(b)(4)	X			
information the trial burn plan must include; Director may require supplemental information	85	270.66(c)	122.66(c)	X			
analysis of each feedstream, as fired	85	270.66(c)(1)	122.66(c)(1)	X			
		270.66(c)(1)(i)	122.66(c)(1)(i)	X			
		270.66(c)(1)(ii)	122.66(c)(1)(ii)	X			
analysis of each hazardous waste, as fired	85	270.66(c)(2)	122.66(c)(2)	X			
		270.66(c)(2)(i)	122.66(c)(2)(i)	X			
		85,94	270.66(c)(2)(ii)	122.66(c)(2)(ii)	X		
analysis of each hazardous waste, as fired	85	270.66(c)(2)(iii)	270.66(c)(2)(iii)	X			

29

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
detailed engineering description of boiler or industrial furnace	85	270.66(c)(3)	122.66(c)(3)	X			
		270.66(c)(3)(i)	122.66(c)(3)(i)	X			
		270.66(c)(3)(ii)	122.66(c)(3)(ii)	X			
		270.66(c)(3)(iii)	270.66(c)(3)(iii)	X			
		270.66(c)(3)(iv)	270.66(c)(3)(iv)	X			
		270.66(c)(3)(v)	122.66(c)(3)(v)	X			
	85,94	270.66(c)(3)(vi)	270.66(c)(3)(vi)	X			
		270.66(c)(3)(vii)	270.66(c)(3)(vii)	X			
	85	270.66(c)(3)(viii)	270.66(c)(3)(viii)	X			
	detailed description of sampling and monitoring procedures	85	270.66(c)(4)	122.66(c)(4)	X		
detailed test schedule for each hazardous waste for which the trial burn is planned	85	270.66(c)(5)	122.66(c)(5)	X			
detailed test protocol	85	270.66(c)(6)	122.66(c)(6)	X			
description of, and planned operating conditions for, any emission control equipment to be used	85	270.66(c)(7)	122.66(c)(7)	X			
procedures for rapid stopping of hazardous waste feed and emissions control if an equipment malfunction	85	270.66(c)(8)	122.66(c)(8)	X			
other information Director finds necessary	85	270.66(c)(9)	122.66(c)(9)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
trial burn conducted to demonstrate conformance with 266.104-266.107 standards under an approved trial burn plan	85	270.66(d)(1)	122.66(d)(1)	X			
findings under which the Director shall approve a trial burn plan	85	270.66(d)(2)	122.66(d)(2)	X			
		270.66(d)(2)(i)	122.66(d)(2)(i)	X			
		270.66(d)(2)(ii)	122.66(d)(2)(ii)	X			
		270.66(d)(2)(iii)	270.66(d)(2)(iii)	X			
		270.66(d)(2)(iv)	270.66(d)(2)(iv)	X			
submit to Director within 90 days of trial burn completion a certification that trial burn was carried out in accordance with approved plan and results of all 270.66(c) required determinations	85	270.66(d)(3)	122.66(d)(3)	X			
submit all data collected during any trial burn	85	270.66(d)(4)	122.66(d)(4)	X			
270.66(d) submissions must be certified by signature of person authorized to sign permit application or 270.11 report	85	270.66(d)(5)	122.66(d)(5)	X			
for DRE trial burn under 266.104(a), Director will specify trial POHCs; basis for specification	85	270.66(e)	122.66(e)	X			
determinations to be made based on each trial burn:	85	270.66(f)	122.66(f)	X			
quantitative analysis of specified materials in the feedstreams	85	270.66(f)(1)	122.66(f)(1)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
determinations needed when a DRE trial burn is required under 266.104(a)	85	270.66(f)(2)	122.66(f)(2)	X			
		270.66(f)(2)(i)	122.66(f)(2)(i)	X			
		270.66(f)(2)(ii)	122.66(f)(2)(ii)	X			
		270.66(f)(2)(iii)	122.66(f)(2)(iii)	X			
quantitative analysis of stack gas and a computation showing conformance with the emission standard when a trial burn is required for chlorinated dioxins and furans under 266.104(e)	85,94	270.66(f)(3)	122.66(f)(3)	X			
quantitative analysis of stack gas and computations showing conformance with applicable emission standards when a trial burn is required for particulate matter, metals, or HCl/Cl <sub>2</sub> under 266.105, 266.106(c) or (d), or 266.107(b)(2) or (c)	85	270.66(f)(4)	122.66(f)(4)	X			
quantitative analysis of scrubber water, ash residues, other residues and products to estimate fate of trial POHCs, metals, and chlorine/chloride when a trial burn is required for DRE, metals or HCl/Cl <sub>2</sub> under 266.104(a), 266.106(c) or (d), or 266.107(b)(2) or (c)	85	270.66(f)(5)	122.66(f)(5)	X			
identification of sources of fugitive emissions and their means of control	85	270.66(f)(6)	122.66(f)(6)	X			
continuous measurement of CO, oxygen, and HC in stack gas	85	270.66(f)(7)	122.66(f)(7)	X			
such other information as Director specifies	85,94	270.66(f)(8)	122.66(f)(8)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
to determine feasibility of compliance with 266.104-266.107 performance standards and adequate operating conditions under 266.103, applicants of existing devices operated under interim status must either prepare and submit a trial burn plan and perform a trial burn or submit 270.22(a)(6) information; submit trial burn results with Part B application if plan approved before Part B submission; date for submission; requirements if submitting trial burn plan with Part B application	85	270.66(g)	122.66(g)	X			
<b>SUBPART G - INTERIM STATUS</b>							
<b>CHANGES DURING INTERIM STATUS</b>							
add new paragraph regarding the addition of newly regulated units if a revised Part A permit application is submitted on or before the date the unit becomes subject to the new requirements	85	270.72(a)(6)	122.72(a)(6)	X			
add new paragraph regarding the addition of newly regulated units under 270.72(a)(6)	85	270.72(b)(7)	122.72(b)(7)	X			
<b>TERMINATION OF INTERIM STATUS</b>							
insert "which has achieved interim status prior to November 8, 1984, interim status terminates" before "on November 8, 1989"	85,94	270.73(f)	122.73(f)	X			

**CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)**

FEDERAL REQUIREMENTS	CHECKLIST REFERENCE	FEDERAL RCRA CITATION	ANALOGOUS STATE CITATION	STATE ANALOG IS:			
				EQUIVALENT	LESS STRINGENT	MORE STRINGENT	BROADER IN SCOPE
insert "which has achieved interim status prior to November 8, 1984, interim status terminates" before "on November 8, 1992"	85,94	270.73(g)	122.73(g)	X			

- 1 Revision Checklist 85 (February 21, 1991; 56 FR 7134) redesignated the old paragraph (d)(2) as (d)(3) and introduced a new paragraph (d)(2) into the code. Revision Checklist 94 (July 17, 1991; 56 FR 32688) made technical corrections to the February 21, 1991 amendatory language for 261.2 and incorrectly redesignated paragraph (d)(3) as (d)(4) and paragraph (d)(4) as (d)(5). The Federal code, as of February 21, 1991, did not include 261.2(d)(3) or 261.2(d)(4). The technical correction addressed by Revision Checklist 96 (August 27, 1991; 56 FR 42504) fixed this error.
- 2 The Federal Register addressed by Revision Checklist 94 designated this paragraph as "261.3(c)(2)(ii)(8)." This is a typographical error; the correct paragraph designation is "261.3(c)(2)(ii)(B)." This error was ultimately corrected by the rule addressed by Revision Checklist 96.
- 3 Note that Revision Checklist 85 made revisions to paragraphs 265.112(d)(2), 265.112(d)(2)(i), 265.112(d)(2)(ii), 265.113(a) and 265.113(b). However, the technical correction addressed by Revision Checklist 96 reversed the revisions made by Revision Checklist 85 and retained the July 1990 CFR language. Thus, States should not make any changes to paragraphs 265.112(d)(2), 265.113(a) or 265.113(b).
- 4 Revision Checklist 112 (57 FR 41566; September 10, 1992) removed and reserved Subpart E of Part 266 and recodified the Subpart E provisions as portions of the new Part 279.
- 5 Note that there is a typographical error in the Federal Register addressed by Revision Checklist 94 (56 FR 32692; July 17, 1991). The "\$266.4" in the heading should be "\$266.40." This error was corrected by Revision Checklist 96 at 56 FR 42512 (August 27, 1991).
- 6 This paragraph was entered into the code by Revision Checklist 85 and was modified by Revision Checklist 96. Subsequently, Revision Checklist 98 issued an administrative stay of the BIF rule as it applies to coke ovens burning certain hazardous wastes from the coke by-products recovery process. This administrative stay was removed by Revision Checklist 105 (57 FR 27880; June 22, 1992). Note also that Revision Checklist 98 incorrectly changed the reference "266.100(b), (c), (d) and (f)" to "266.100(b), (c) and (d)." This error was corrected by Revision Checklist 111 at 57 FR 38564 (August 25, 1992).
- 7 Revision Checklist 112 (57 FR 41566, September 10, 1992) removed and reserved Subpart E of Part 266 and recodified the Subpart E provisions as portions of the new Part 279. To reflect this change, Revision Checklist 112 revised 266.100(b)(1) to refer to Part 279 rather than Subpart E of Part 266.

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

- 8 Note that the Federal Register addressed by Revision Checklist 85 designated this paragraph as "266.102(d)(4)(D)." This is a typographical error; the correct designation is "266.102(d)(4)(iv)." See technical correction at 56 FR 32688 (July 17, 1991; Revision Checklist 94).
- 9 There seems to be an error in the Federal Register addressed by Revision Checklist 85. Federal code refers to "particulate matter standard in § 266.111(b)," but 266.111(b) addresses definitions of "direct transfer equipment" and "container," not particulate matter standards. It appears that the Federal code should likely reference 266.105(a) as it does contain a particulate matter standard.
- 10 Note that in the February 21, 1991 rule addressed by Revision Checklist 85, the subparagraph designation was not italicized. This is a typographical error. The August 27, 1991 (56 FR 42504; Revision Checklist 96) technical correction fixes this error.
- 11 Note that the August 27, 1991 Federal Register, which addressed the technical correction for this citation, has a typographical error; the reference to "266.102(e)(4)(iii)(c)(1) and (2)" in this citation should be "266.102(e)(4)(iii)(C)(1) and (2)."
- 12 Note that in the Federal Register for Revision Checklist 85, the subparagraph designation was not italicized. This is a typographical error. The 56 FR 32688 (July 17, 1991; Revision Checklist 94) technical correction fixes this error.
- 13 Note that the July 1, 1992 CFR inadvertently omitted the text to 266.103(c)(1)(i)-(xiii) and 266.103(c)(3)(ii)-(iii)(C) from the Federal code. States should incorporate these paragraphs, as found in the Federal Register addressed by Revision Checklist 85 (56 FR 7134; February 21, 1991), and amended by Revision Checklist 94 (56 FR 32688; July 17, 1991).
- 14 In the Federal Register addressed by Revision Checklist 85, the designation for this subparagraph is 266.104(g)2. This is a typographical error; the correct designation is 266.104(g)(2). See the technical correction at 56 FR 32689 (July 17, 1991; Revision Checklist 94).
- 15 Note that there is an error in the Federal Register for Revision Checklist 111 (57 FR 38558; August 25, 1992) for this rule. The phrase "dispersion modeling to predict the maximum annual average off-site ground level contamination for each" appears twice but should only occur once.
- 16 In the Federal Register addressed by Revision Checklist 85, the designations for these subparagraphs are 266.107(d)(i) and 266.107(d)(ii) (see 56 FR 7225). These are typographical errors. The subparagraphs should be designated 266.107(d)(1) and 266.107(d)(2). See technical corrections at 56 FR 32690 (July 17, 1991; Revision Checklist 94).
- 17 In the Federal Register addressed by Revision Checklist 85, the section designation for regulation of residues is 266.122 (see 56 FR 7227). This is a typographical error and the section should be designated 266.112. Revision Checklist 94 corrects this error at 56 FR 32688 (July 17, 1991).
- 18 Note that Revision Checklist 96 replaced the old paragraph introduced into the code by Revision Checklist 85.

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

- 19 Note the typographical error in the Federal Register for Revision Checklist 127 [58 FR 59598 (November 9, 1993)]: "FO39" should be "F039" (i.e., should be a zero not an upper case "O").
- 20 Note that Revision Checklist 94 replaced the old Table introduced into the code by Revision Checklist 85.
- 21 Note that Revision Checklist 85 simply makes an announcement concerning the publishing of the Appendix at a future time. The Appendix was actually entered into the code by Revision Checklist 94. Subsequently, sections 7.0 and 9.2 were modified by Revision Checklist 96; section 5.0 was modified by Revision Checklists 111 and 114, and section 6.0 was modified by Revision Checklist 111.
- 22 Note that there are errors in the Federal Register for Revision Checklist 111 (57 FR 38558; August 25, 1992) for this rule. The original titles for these tables in the July 17, 1991 rule (56 FR 32688; Revision Checklist 94) read " $\mu\text{G}/\text{M}^3$ ", not " $8\text{G}/\text{M}^3$ " as indicated in the corrections numbered 11 and 12 on page 38566 of the Federal Register for Revision Checklist 111. The " $8\text{G}/\text{m}^3$ " however, appears in the 1991 CFR and is incorrect. These errors were corrected by Revision Checklist 114 (57 FR 44999, September 30, 1992). The " $\mu\text{G}/\text{m}^3$ " in the July 16, 1991 Federal Register and the " $8\text{G}/\text{m}^3$ " in the 1991 CFR should read " $\mu\text{g}/\text{m}^3$ " not " $\text{g}/\text{m}^3$ " as shown at 57 FR 38566 (August 25, 1992).
- 23 Note that Revision Checklist 96 replaced the old section 7.0 introduced into the code by Revision Checklist 94.
- 24 Note that Revision Checklist 85 simply makes an announcement concerning the publishing of the Appendix at a future date. The Appendix was actually entered into the code by Revision Checklist 94.
- 25 This appendix was originally introduced by Revision Checklist 94; Revision Checklist 85 merely announced that the appendix would be published at a future date. Revision Checklist 125 removed Part 266 Appendix X and Appendices A, B and C to Appendix X, "Guidelines on Air Quality Models (Revised)" and changed references to the guidelines in Part 266 to refer to 40 CFR Part 51, Appendix W.
- 26 Note that this is the same section of code which contained the specific Part B information requirements for the Wood Preserving listing (55 FR 50450). Thus, the Part B boilers/industrial furnace requirements were added so that the Part B information requirements for drip pads were inadvertently removed by the rule addressed by Revision Checklist 85 (56 FR 7134; February 21, 1991). On July 1, 1991 (56 FR 30192; Revision Checklist 92) a technical correction was published moving the wood preserving requirements to 270.26.
- 27 States only need to make changes if they have adopted, or plan to adopt, the provisions addressed by Revision Checklist 54 (53 FR 37912), because 270.42 is not required by 271.14 to be part of a State's permitting program.

CONSOLIDATED CHECKLIST: Burning of Hazardous Waste in  
Boilers and Industrial Furnaces as of June 30, 1994 (cont'd)

- 28 The paragraph following 270.42(g)(1)(v) in Federal code, i.e., 270.42(g)(2), is included in the Federal Register for Revision Checklist 85-(56 FR 7237, February 21, 1991). However, no changes were made to the paragraph by the February 21, 1991 rule, so it has not been included in this consolidated checklist.
- 29 Note that Revision Checklist 126 (58 FR 46040; August 31, 1993), amended 270.66(c)(2)(i)&(ii) by replacing the reference to 270.6 with a reference to 260.11 as incorporated by reference at both 260.11 and 270.6.