

US EPA ARCHIVE DOCUMENT

1. Incident Name		2. Date Prepared	3. Time Prepared	UNIT LOG ICS 214	
Kalamazoo River/Enbridge Spill		06/06/2012	1900		
4. Unit Name/Designators		5. Unit Leader		6. Operational Period :	
Operations Unit/Submerged Oil Task Force #2		Name:	Dan Capone & Joe Victory (START/US EPA)	From:	06/06/2012 0700
		Position:	Operations Section Chief/Deputy	To:	06/06/2012 1900
7. Personnel Roster Assigned					
<u>Name</u>		<u>ICS Position</u>		<u>DUTY CELL</u>	
Dan Capone		Operations Section Chief			
Joe Victory		Operations Section Deputy			
Dan Zahner		Field Team Lead			
Jonathan Roubik		SOTF2			
8. Activity Log					
Activity Area	29.10N, 29.15N, 29.18T, 29.28T, 29.70T			LAT	LAT
				Various	Various
				(DD.MMMM)	(DD.MMMM)
<u>OIL OBSERVED</u>	EXTENT OF OIL IMPACTED AREA				
	DENSITY OF OIL /SHEEN				
Total Collection Points	N/A				
Total Boom Deployed	N/A				
Activity	<p><u>Weston/START Submerged Oil Branch Task Force Group (SOTF) Team Activity:</u></p> <p>SOTF#2 Jonathan Roubik (START), Team Lead Eric Oleson, and Leica operator Eric Celebreeze performed (or attempted) poling at 46 locations in focus areas 29.10N, 29.15N, 29.18T, 29.28T, 29.70T. Poling activities had 1 location that produced an overall submerged oil category of heavy sheen concentration (29.70T-B-01). 8 locations produced moderate sheen (in areas 29.10N, 29.18T and 29.70T). 19 locations produced an overall submerged oil category of light sheen and 17 locations produced no sheen. 1 location was dry and unable to be poled.</p> <p>Data for all sites was collected following a temperate reading. (See field log for details) Sediment temperatures ranged from 54.0 to 71.2 degrees F, above sediment temperatures ranged from 53.8 to 70.6 degrees F, and surface water temperatures ranged from 53.8 to 70.5 degrees F.</p>				
Health and Safety Issues					
Comments	<p>Locations in which the boat motor kicked up more sheen than poling activities were recorded with the greater number globule count/sheen concentration.</p> <p>Sheen was collected by use of soft boom placed at downstream ends of poling channels during poling ops.</p> <p>Boats used in areas where moderate or heavy sheen was observed were decontaminated onsite at the end of the day.</p>				