

US EPA ARCHIVE DOCUMENT

1. Incident Name		2. Date Prepared	3. Time Prepared	UNIT LOG ICS 214	
Kalamazoo River/Enbridge Spill		06/14/2012	1900		
4. Unit Name/Designators		5. Unit Leader		6. Operational Period :	
Operations Unit/Submerged Oil Task Force #2		Name:	Dan Capone & Joe Victory (START/US EPA)	From:	06/14/2012 0700
		Position:	Operations Section Chief/Deputy	To:	06/14/2012 1900
7. Personnel Roster Assigned					
<u>Name</u>		<u>ICS Position</u>		<u>DUTY CELL</u>	
Dan Capone		Operations Section Chief			
Joe Victory		Operations Section Deputy			
Dan Zahner		Field Team Lead			
Jonathan Roubik		SOTF2			
8. Activity Log					
Activity Area	25.41LDB and 26.85 RDB			LAT	LAT
				Various	Various
				(DD.MMMM)	(DD.MMMM)
<u>OIL OBSERVED</u>	EXTENT OF OIL IMPACTED AREA				
	DENSITY OF OIL /SHEEN				
Total Collection Points	N/A				
Total Boom Deployed	N/A				
Activity	<p><u>Weston/START Submerged Oil Branch Task Force Group (SOTF) Team Activity:</u></p> <p>SOTF#2 Jonathan Roubik (START), Team Lead Eric Oleson, and Yuma operator Eric Celebreeze performed (or attempted) poling at 12 locations in focus area 26.85RDB and one ring test at 25.41LDB. Poling activities showed the following results:</p> <p><u>25.41LDB (1 Ring Test location)</u> 1 location produced light sheen (25.41LDB-B-08)</p> <p><u>26.85RDB (12 locations)</u> 1 locations that produced heavy sheen concentration (26.85RDB-B-02) 4 locations produced moderate sheen (26.85RDB-B-07, 06, 04 and 01) 7 locations produced light sheen 0 locations produced no sheen 0 locations were dry and unable to be poled</p> <p>Data for all sites was collected following a temperate reading that exceeded the 60 degree Fahrenheit temperature requirement:</p> <p>Sediment temperatures ranged from 66.7 to 75.0 degrees F. Above sediment temperatures ranged from 66.7 to 73.9 degrees F. Surface water temperatures ranged from 71.4 to 84.2 degrees F.</p>				

Health and Safety Issues	
Comments	David Richardson of Tetra-Tech completed demonstration of ring testing for poling groups today at 25.41LDB. David discussed SOP with the group including a 6" water depth that should be allowed to sit and soak into the sediment for 10 minutes prior to poling. Temperatures should be taken of the sediment prior to filling ring with water and also of water temperature prior to poling. Also, any loose debris or vegetation should be removed. Following this procedure, poling should continued as completed as for submerged oil reassessment.